

Residential Tent 30 m²

Design code: RT30

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
1	<ul style="list-style-type: none"> • Supply, deliver and install a 30 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 8 steel columns 200cm, 2mm thickness, 1.5" diameter. • 3 steel columns 263cm high 2mm thickness, 1.5" diameter. • 4 steel arcs 2mm thickness, 1.5" diameter. • 15 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of Blackout plastic cover consists of plastic sheets of Italian/ Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof, light proof, flame retardant and UV protection. - Weight: 800 gr/ m2, - Tensile strength: 2700 N/5 cm - Tear resistance: 300 N - Adhesion: 80 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Doors opening should be (200x100 cm), windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • Inner cover should be heavy Maly fabric (drill) minimum percentage of cotton 80%, fixed to the steel frame by plastic fasteners, and holes should be opened with steel rings every 50 cm. • The price includes the supply and install of a fastening rope of type (Massess 8mm). • 14 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. 	L.S	10		

<ul style="list-style-type: none">•Supply and deliver plastic mat (Hasera): 4m x 5m• The contractor must implement the project according to the technical drawings. and the project supervisor instructions.• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.•Supply and Install curtains separators in the middle of the tent as indicated in the drawings. Type and color as approved by the Engineer.•Supply and deliver a Hammer for each tent.				
--	--	--	--	--

Residential Tent **40 m²**

Design code: RT40

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
2	<ul style="list-style-type: none"> • Supply, deliver and install a 40 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 10 steel columns 200cm, 2mm thickness, 1.5" diameter. • 3 steel columns 263cm high 2mm thickness, 1.5" diameter. • 5 steel arcs 2mm thickness, 1.5" diameter. • 20 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of Blackout plastic cover consists of plastic sheets of Italian/ Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof, light proof, flame retardant and UV protection. - Weight: 800 gr/ m2, - Tensile strength: 2700 N/5 cm - Tear resistance: 300 N - Adhesion: 80 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Doors opening should be (200x100 cm), windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • Inner cover should be heavy Malty fabric (drill) minimum percentage of cotton 80%, fixed to the steel frame by plastic fasteners, and holes should be opened with steel rings every 50 cm. • The price includes the supply and install of a fastening rope of type (Massess 8mm).	L.S	20		

<ul style="list-style-type: none">• 16 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings.• Supply and deliver of two plastic mat (Hasera): (4m x 5m) x 2• The contractor must implement the project according to the technical drawings. and the project supervisor instructions.• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.• Supply and Install curtains separators in the middle of the tent as indicated in the drawings. Type and color as approved by the Engineer.• Supply and deliver a Hammer for each tent.				
---	--	--	--	--

Residential Tent **60 m²**

Design code: RT60

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
3	<ul style="list-style-type: none"> • Supply, deliver and install a 60 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 14 steel columns 200cm, 2mm thickness, 1.5" diameter. • 4 steel columns 263cm high 2mm thickness, 1.5" diameter. • 7 steel arcs 2mm thickness, 1.5" diameter. • 30 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of Blackout plastic cover consists of plastic sheets of Italian/ Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof, light proof, flame retardant and UV protection. - Weight: 800 gr/ m2, - Tensile strength: 2700 N/5 cm - Tear resistance: 300 N - Adhesion: 80 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Doors opening should be (200x100 cm), windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • Inner cover should be heavy Malty fabric (drill) minimum percentage of cotton 80%, fixed to the steel frame by plastic fasteners, and holes should be opened with steel rings every 50 cm. • The price includes the supply and install of a fastening rope of type (Massess 8mm).	L.S	5		

<ul style="list-style-type: none"> • 20 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. • Supply and deliver of three plastic mat (Hasera): (4m x 5m) x 3 • The contractor must implement the project according to the technical drawings. and the project supervisor instructions. • The contractor must install and fix the tent in the ground with all needed ropes and steel angles. • Supply and Install curtains separators in the middle of the tent as indicated in the drawings. Type and color as approved by the Engineer. • Supply and deliver a Hammer for each tent. 				
--	--	--	--	--

Livelihood Tent 20 m²

Design code: LT20

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
4	<ul style="list-style-type: none"> • Supply, deliver and install a 20 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 6 steel columns 200cm, 2mm thickness, 1.5" diameter. • 2 steel columns 263cm high 2mm thickness, 1.5" diameter. • 3 steel arcs 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 10 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of PVC plastic cover consists of plastic sheets of Italian/Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof and flame retardant. - Weight: 650 gr/ m², - Tensile strength: 2100 N/5 cm - Tear resistance: 350 / 280 N - Adhesion: 60 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • The price includes the supply and install of a fastening rope of type (Massess 8mm). • 12 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. • The contractor must implement the project according to the technical drawings. and the project supervisor instructions. 	L.S	5		

	<ul style="list-style-type: none">• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.• Supply and deliver a Hammer for each tent.				
--	---	--	--	--	--

Livelihood Tent 40 m²

Design code: LT40

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
5	<ul style="list-style-type: none"> • Supply, deliver and install a 40 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 10 steel columns 200cm, 2mm thickness, 1.5" diameter. • 3 steel columns 263cm high 2mm thickness, 1.5" diameter. • 5 steel arcs 2mm thickness, 1.5" diameter. • 20 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of PVC plastic cover consists of plastic sheets of Italian/Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof and flame retardant. - Weight: 650 gr/ m2, - Tensile strength: 2100 N/5 cm - Tear resistance: 350 / 280 N - Adhesion: 60 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • The price includes the supply and install of a fastening rope of type (Massess 8mm). • 16 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. • The contractor must implement the project according to the technical drawings. and the project supervisor instructions. 	L.S	15		

	<ul style="list-style-type: none">• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.• Supply and deliver a Hammer for each tent.				
--	---	--	--	--	--

Livelihood Tent 60 m²

Design code: LT60

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
6	<ul style="list-style-type: none"> • Supply, deliver and install a 60 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 14 steel columns 200cm, 2mm thickness, 1.5" diameter. • 4 steel columns 263cm high 2mm thickness, 1.5" diameter. • 7 steel arcs 2mm thickness, 1.5" diameter. • 30 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of PVC plastic cover consists of plastic sheets of Italian/ Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof and flame retardant. - Weight: 650 gr/ m2, - Tensile strength: 2100 N/5 cm - Tear resistance: 350 / 280 N - Adhesion: 60 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • The price includes the supply and install of a fastening rope of type (Massess 8mm). • 20 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. • The contractor must implement the project according to the technical drawings. and the project supervisor instructions. 	L.S	10		

	<ul style="list-style-type: none">• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.• Supply and deliver a Hammer for each tent.				
--	---	--	--	--	--

Kitchen Tent 20 m²

Design code: KT20

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
7	<ul style="list-style-type: none"> • Supply, deliver and install a 60 m² tent according to the following specifications: <ul style="list-style-type: none"> 1) Steel works: Welding must be CO2 welding in lines, not points, and it must be painted with anti-corrosion coating with the color of the galvanized pipes: <ul style="list-style-type: none"> • 6 steel columns 200cm, 2mm thickness, 1.5" diameter. • 2 steel columns 263cm high 2mm thickness, 1.5" diameter. • 3 steel arcs 2mm thickness, 1.5" diameter. • 8 steel horizontal pipes 200 cm long 2mm thickness, 1.5" diameter. • 10 steel horizontal pipes 250cm long 2mm thickness, 1.5" diameter. 2) PVC cover: <ul style="list-style-type: none"> • Fabricate and supply of Blackout plastic cover consists of plastic sheets of Italian/ Turkish type according to the following specifications: <ul style="list-style-type: none"> -Water proof, light proof, flame retardant and UV protection. - Weight: 800 gr/ m², - Tensile strength: 2700 N/5 cm - Tear resistance: 300 N - Adhesion: 80 - Abrasion: > 20.000 (revs). - Handling Temperature Range: (- 30°C / + 70°C) - Color: Caramel (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds), considering sewing a belt property inside the pleat with the sewing machine set to the largest number of Walters per centimeters. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • Front sides are sewed with upper cover. Upper cover has 40 cm extra width from both long sides and 5cm "scotch" to ensure total closing of the tent. Long side covers must have rings to fix it with the horizontal and vertical pipes with extra-long 40cm and with "scotch" from both sides; in order to be able to fix the tent with stones and dirt. • Doors opening should be (200x100 cm), windows openings (80x80 cm), as per specifications, drawings and the project supervisor instructions. • The price includes the supply and install of a fastening rope of type (Massess 8 mm). • 12 steel angles (5x5x75 cm) has to be fixed in the ground according to the technical drawings. • The contractor must implement the project according to the technical drawings. and the project supervisor instructions. 	L.S	10		

	<ul style="list-style-type: none">• The contractor must install and fix the tent in the ground with all needed ropes and steel angles.• Supply and deliver a Hammer for each tent.				
--	---	--	--	--	--

Fabricate and supply PVC sheets

Price includes wages, material, accessories, fabrications and supplying in the desired location for every unit, where all materials must be approved by the Engineer and considered as a sample, before fabricating the following items:

No.	Item	Unit	Quantity	Unit Price (Dollar)	Total Price (Dollar)
8	<p>Fabricate and supply of PVC Sheets according to the following specifications:</p> <ul style="list-style-type: none"> • Fabricate and supply of Blackout plastic cover consists of plastic sheets (waterproof) of Italian/ Turkish type with 650 gr/ m2 density, caramel color (semi brown). • Sheets lines are to be welded together with a high frequency technique, where welding should be executed along with the sheet width (2m side), and weld a belt of 5 cm width above the connection line. • Outside edges are to be folded twice (2 folds at least), considering sewing a belt properly inside the pleat with the Sewing machine set to the largest number of stitches per centimeter. • Sewing one buttonhole every meter length on all sides, with the sewing machine set to the largest number of Walters per centimeter. • The price includes the supply of a fastening rope of type (Massess), with length of 50m and 8 mm/ structure. • Steel rings 1 mm have to be attached with PVC cover/ 2 meter. • The cover's dimension will be designed to fit shed structures. • Taking measurements for all structures is under contractor responsibility. • Doors and windows openings should be fitted with all existing openings. • The Contractor shall deliver the required material to any location in West-Bank (without installation). • The delivery period is one week from the date of notice. 	m ²	300		

Summary of Prices

No.	List of Items	Total (Dollar)
1	Residential Tent 30 m ²	
2	Residential Tent 40 m ²	
3	Residential Tent 60 m ²	
4	Livelihood Tent 20 m ²	
5	Livelihood Tent 40 m ²	
6	Livelihood Tent 60 m ²	
7	Kitchen Tent 20 m ²	
8	Fabricate and supply PVC sheets	
TOTAL		

Total in words:

Name _____ الإسم

Position: _____ الوصف الوظيفي

Signature & Stamp: _____ التوقيع والختم

Date: _____ التاريخ