

International CALL FOR TENDER ACTED **OPT** Part A - Instructions to bidders

Date: 20/12/2020

Tender N°: T/HIP2021/EmergencyMaterials/RAM/20-12-2020/001

ACTED oPT is requesting through this tender a company to provide detailed written quotations for the supply of the following products:

PRODUCT SPECIFICATIONS:

- 1. Description:
- 2. Product class / category:
- 3. Made in (product origin):
- 4. Product stage:
- 5. INCOTERM (delivery conditions):
- 6. Quantity/unit:
- 7. Packaging requested:

Emergency Materials Emergency Materials National/International New, In good condition, Ready to be used DDP/To various locations in West Bank based on need see the detailed BoQ attached see the detailed BoQ attached

Lot	Description	Qty	Unit	INCOTERMS/ Delivery point	Delivery deadline
1	Supply and Installation of Residential Block Structure 32 m ² , Residential Block Structure 48 m ² , Residential Block Structure 32 m ² – without Toilet: Residential Block Structure 48 m2 – without Toilet: Fixed Latrine, Fixed PWD Latrine	See deta BoQ	iled	All of west Bank	To be indicated on the contract.

RESPONSIBILITIES OF THE CONTRACTOR:

- 1. Terms of delivery: DDP + to be indicated in the contract
- 2. Date of delivery: <u>The contractor shall supply and install the required items within 7 days</u> from receiving the Call-off purchase order.
- 3. Validity of the offer: 12 months

The answers to this tender should include the following elements:

- A written quotation including all the product specifications, the price per unit, quantity proposed and unit, and total price; (Compulsory)
- > A certificate of origin.
- > A copy of the ID of the legal representative of the company. (Compulsory)
- > A Copy of the registration certificate of the company.(Compulsory)

Questions regarding the technical or administrative requirements of this International National Call for Tender may be submitted no later than 12:00 pm local Ramallah time on Sunday 27th of December, 2020 by email to <u>opt.tender@acted.org</u>.



GENERAL CONDITIONS:

- 1. All bids must be submitted before 03 / 01 / 2021 at 12:00pm By EMAIL Only to opt.tender@acted.org
- 2. Tenderers will fill, sign, stamp and return the Offer form according to ACTED's format. All prices should be in USD, Excluding TAX (compulsory).
- 3. Tenderers will sign and return all pages of the Product Specifications for which they apply.
- 4. The offer to the call for tender will not result in the award of a contract.
- 5. The offer must be submitted to ACTED purchase department in a sealed envelope with the mention of the tender reference on the envelope: T/HIP2021/EmergencyMaterials/RAM/20-12-2020/001
- 6. The tenderers can submit an offer for one or several lots.
- 7. T/HIP2021/EmergencyMaterials/RAM/20-12-2020/001 not to be opened before 03/01/2021 at 12:00PM
- 8. Unsealed envelopes and late offers will not be considered.
- 9. To ensure that funds are used exclusively for humanitarian purposes and in accordance with donors' compliance requirements, all contract offers are subject to the condition that contractors do not appear on anti-terrorism lists, in line with ACTED's anti-terrorism policy. To this end, contractors' data shall be automatically processed.
- 10. Suppliers can bid for one or more of the lots. Suppliers must bid for all items within each selected lot.
- 11. The tender advertisement fees will be deducted from winners of each of the Lots based on proportion of the estimated contract amount.

NOTE: ACTED adopts a zero tolerance approach towards corruption and is committed to respecting the highest standards in terms of efficiency, responsibility and transparency in its activities. In particular, ACTED has adopted a participatory approach to promote and ensure transparency within the organization and has set up a Transparency focal point (Transparency Team supervised by the Director of Audit and Transparency) via a specific e-mail address. As such, if you witness or suspect any unlawful, improper or unethical act or business practices (such as soliciting, accepting or attempting to provide or accept any kickback) during the tendering process, please contact the following send an e-mail to transparency@acted.org.

SPECIFIC CONDITIONS:

- 1. Eligible contractor should be registered at PCU (Palestinian Contractors Union). (compulsory)
- 2. Eligible contractor should be registered at the VAT and customs department and has the ability to provide ACTED with Zero VAT bills. (compulsory)
- 3. Eligible contractor should provide VAT registration number and financial clearance certificate.
- 4. Eligible contractor needs to be able to issue tax bills. (compulsory)

5. Eligible contractor should provide valid professions practicing license registration certificate from the Companies' Controller. (compulsory)

- 6. ACTED has the right to split or cancel or postpone or extend the tender.
- 7. ACTED is not bound to accept the lowest price.

8. Eligible contractor for the tender needs to secure entry of a tender worth **5,000 US \$** as a bank guarantee valid for 90 days starting from the closing date of the tender or a certified check bank, where personal checks or cash are not accepted. (compulsory)



9. Upon the signing of the contract, winning contractor for the tender needs to secure a performance guarantee Valid for 1 year worth 10% of the total estimated amount in the BOQ US or a certified check bank for the same amount, where personal checks or cash are not accepted. (compulsory)

- 10. All prices should be in USD Excluding Tax. (compulsory)
- 11. The contract duration is 12 months, and supply will be requested throughout the project's duration.
- 12. Fees of tender advertising in newspapers will be charged to the winner bidder(s).
- 13. The selection criteria will be based on a **70% Financial and 30% Technical**.

Company Name:	
Authorized Representative Name:	

Signature

Stamp:



Evaluation Criteria

A supplier will be selected based on the selection criteria from the table below (with a maximum score of 100). The Scoring Method will be based on the submitted bid .

CRITERIA	SCORING METHOD	MAXIMUM SCORE AVAILABLE	
Price	Up to 70 points can be awarded based on the price of requested works	70	
Reliability	Up to 10 points can be awarded for suppliers with a demonstrated good record of delivery with NGOs and experience in the sector:	10	
	1 point will be allocated for each project (More than 20,000 USD) with other NGOs.		
	Required providing a summary table of projects + Certificate		
Capacity	- 2 Point will be allocated for each key staff member for each of the following: Project Manager, Civil or Mechanical Engineer, Forman (Maximum 6 Points).	10	
	- 2 Points will be allocated if the work team includes from 1 -3 workers.4 Points for teams with 4 or more workers (Maximum 4 Points)		
	* CV for key staff is requires		
	*Organizational chart	10	
	*Table of Company Team		
Previous experience	Up to 10 points can be awarded for suppliers with previous experience in similar rehabilitation projects:	10	
	1 point will be allocated per each year of experience in project implementation (The duration of each project must be provided in the summary table).		



Part B - OFFER FORM ACTED OPT

Date: 20/12/2020

Tender N°: T/HIP2021/EmergencyMaterials/RAM/20-12-2020/001

To be Filled by Bidder (COMPULSORY)

Details of Bidding Company:

1.	Com	ipany Name:	(<u>)</u>
2.	Com	pany Authorized Representati	ve Name: <u>(</u>)
3.	Com	pany Registration No:	()
		No/C	Country/ Ministry	
4.	Com	pany Specialization:)
5.	Maili	ing Address:	()
		Country/Governorate./C	City/St name/Shop-Office No	
	a.	Contact Numbers:	(Land Line:	/ Mobile No:
)		
	b.	E-mail Address:	()

I undersigned ______, agree to provide ACTED, non-profit NGO, with items answering the following specifications, according to the general conditions and responsibilities that I engage myself to follow.

<u>*This Tender leads to frame Work Agreement with a period of 12 moths. The quantities mentioned are just an estimation (Quantity might vary).</u>



LOT 1: BLOCK STRUCTURES

Residential Block Structure 32 m²

Design code: BS32

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

This is a quick construction technique, the work in site should be executed maximum within 7 days from receiving the Call-off purchase order.

 Reinforced concrete B-250 floor slabs with ground beams: Supply, mix and cast reinforced concrete floor slab grade 'B 250' of cement content not less than 300 kg and reinforcement steel (8mm bars every 20cm in both directions. Including the ground beams with their reinforcement steel. Price to include formwork, reinforcement, installing of plastic sheets between the concrete and the ground, curing and all necessary works. Do all required excavating and filing in order to obtain levelled ground with zero level slopes under the structures and in the school yard. Excavation to any depth in any type of soil including rock. To use selected materials under the structural elements (beams and columns) and school yard. Price to include levelling compacting and watering. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. 	
Concrete block works: Supply and build concrete block walls, Grade 35 of high quality standards with block dimensions (40x20x15) cm according to the detailed drawings and supervisor engineer instructions; Block works include:- -Vertical and horizontal joints. -Cement and mortar. -Galvanized angles butterfly ties (at joints and between walls with different materials. -Lintels and bond beams to the full length of the wall with minimum height of 20 cm and in the same wall thickness of reinforced concrete grade B-200 with due reinforcement steel, on top of doors and windows or as specified per drawings. -All needed materials and work to complete job as per drawings, specifications and supervisor engineer instructions. Internal and external plastering: -Supply and apply internal and external plaster of natural thermal insulation plaster Styronit type (STY 160 KABA) or equivalent mixed with mega bond. -Thermal Conductivity: 0,048 W/(m.K). -Plastering works should be in two layers, the final one is for fair finish face. The total plaster thickness should be 1.0-1.5 cm. -All according to the specifications, detailed drawings and supervisor engineer instructions. -Steel angle should be installed in each corner internally and externally. Marble window frames (lentils): -Supply and install local made Scm thick marble frame for all windows' sides,	



-The windows and frames must be prepared before starting the		
implementation in site to ensure the quick implementation of the new		
structures.		
All according to the specifications, detailed drawings and ACTED supervisor		
engineer instructions.		
Toilet tiles:		
-Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish.		
Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with		
same marble chipping, bedding and jointing in cement and sand mortar with		
ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah		
or sand fill, and on site grinding where required, polishing and cleaning. (colors		
according to supervisor engineer instructions).		
-Works to include supply, install and finish two (3 cm thick) marble door, the		
width of lintels must be same as the wall thickness.		
- Walls tile size : 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should		
be tiled fully from the ground to roof).		
- Floor tile : 20 x 40 x .9 cm, Turkish brand or equivalent,		
-All according to the specifications, detailed drawings and supervisor engineer		
instructions.		
Marble Door threshold:		
-Works to include supply, install and finish one (5 cm thick) marble Door		
threshold, the width of lintels must be the same as the wall depth.		
Future land		
External roof:		
Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white		
for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with		
F20 of compression .The boards' dimensions are (230x117x5) cm, and they are		
fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with		
thickness of 3mm from all sides. All fixed by special screws and elastic rubber to		
prevent water leakage according to the detailed drawings. Board weight must		
be at least 10 kg/sqm.		
Galvanized profiles as indicated below:		
Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the		
drawing.		
Supply and install a connected steel beam (8 x 4), and 2mm thick which has to		
be installed inside the bond beam as indicated in the drawings.		
- Galvanized steel U angles (1.5mm thick), welded together and fixed correctly		
on the top (roof side) of the gathered zinc boards for each facade, and same for		
all internal partitions and where needed.		
System fixation		
It will be pre-prepared, using the CO2 method welding in lines. For the profiles		
and U angle intersections, welding should be done at the site only when		
needed; taking into consideration the unit should consist of several complete		
parts to be joined at the site either by specified welding method or using		
drilling with 8 mm diameter screws.		
Off white Aluminum windows		
Off-white Aluminum windows		
-4 Windows (120 x 120) cm, model No.7700 of national industry, and of 4 mm		
thickness double glass framed by Aluminum profile with a movable galvanized		
steel external mosquito netting on the whole window. (Three portions).		
-1 Window (60 x 60) cm, model No.4000 of national industry, and of 4 mm thickness (Mobazzar) glass framed by Aluminum profile with a movable		
galvanized steel external mosquito netting on the whole window.(Three		
portions).		
por donsy.		
Windows Protections		



Supply and implement spear shaped protection for every window in shelter unit, where the protection steel is to be painted with three coats (one primer coat) with the color approved by the Supervisor Engineer. Steel bars; dimensions 10 mm with spacing distance of 12 cm between spears.	
 Wooden doors (90x200x5) cm Supply and install 2 wooden doors with the following specifications: The door shall be made from sandwich boards 17 mm in both sides consisting of pinewood strips placed end to end. The width of each strip shall not exceed 25 mm. The strips shall be placed side by side, which shall then be glued between the two wooden layers from each side (Sandwich and beech layers). The surface shall be made from Swedish wood with square and flat shape, the corners of frame being fabricated to a true right angle. Both the fixed and opening frames shall be constructed of sections which have been cut to length, mitered and screwed at the corners. Good quality of door handle attached with lever lock operated by key and lockable from both inside and outside 	
 Steel Door (100x200x5) cm Supply and install a steel door with the following details: The door shall be made from Galvanized steel sheets 2 mm in both sides consisting (Internal and external), in addition to two steel frames from outside. The surface shall be painted twice (Primer layer and grey color) Frames shall be manufactured out of (2 mm) Galvanized Steel box 6x3 cm. Good quality of door handle attached with lever lock operated by key and lockable from both inside and outside 	
ToiletTurkish or European (Based on request)Turkish toilet: (45*55) cm, caramel color correctly connected to plastic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent.OREuropean Water toilet Caramel color correctly connected to ceramic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent.	
Water tap Water tap of type Chrome (long neck) of first grade (Italian or equivalent), which installed on the basin itself.	
Basin Caramel Basin (45*55) cm of type Italian brand or equivalent.	
Shower base Shower base fabricated from metal sheet coated with PVC layer with a clear resulted area of (80*80) cm, 2mm thickness fixed on steel base with specifications as shown in the attached drawings, (see detail BS32). (Shower room should be elevated with 20 cm, from the shelter level)	
Shower tape Single chrome tap with double use (tape and shower hand) of first grade (Italian or equivalent),	
 Piping Connecting 2" PVC pipes and needed fitting with suitable length for the shower and kitchen for the purpose of drainage, and 16 mm diameter HDPE pipes for water supplying. The contractor should supply and install buried drilled barrel for drainage. Connecting 4" PVC corrugated HDPE pipes and needed fitting with 10-meter length as sewer connection. Supply galvanized Steel Stand for Water tank (See the drawings BS32) 	
- Supply transfer, and install polyethylene water tank Size 1 m3:	



-The Water Tank must be made by blow molding method.	
-The water tank must be free of any holes.	
-Water Tank must be made of LLDPE materials in White color.	
-Water tank must have 7 internal rings at least with 1 cm depth for each ring.	
-Water Tank Durability 30 years at least.	
-Water Tank wall thickness must not be less than (7) mm, with four layers of	
polyethylene, (White: 2.8 mm, Black: 1.4 mm, Red: 1.4 mm, Blue: 1.4 mm).	
- color must be White.	
- The water tank must be free of any holes	
The water tank must be nee of any notes	
- Connect the structure (Including toilet and kitchen) and the mobile latrine	
with the above-mentioned water tank using HDPE pipes up to 12m long	
(depends on the real distance in each case) Installing and connecting the	
system should be implemented correctly to have the system operating.	
system should be implemented correctly to have the system operating.	
-Supply and install water collectors with include XLPE Pipe 16mm, oven painted	
aluminum cabinet with two doors, valves for branches, main valves, vents, and	
all accessories.	
Installation of 80 cm long kitchen unit.	
Stainless Steel basin 120 cm, and sandwich wooden cabinets, with Italian joints	
or equivalent as shown in the drawings, a good quality cabinet hand, single	
Chrome long neck tap of first grade (Italian or equivalent) fixed to the basin,	
and connecting the required water supplying plastic pipes (20 mm diameter),	
and 2" PVC sewage pipe connected to the sewer tank.	
Roof water gutter	
Supply and install roof gutter at lowest edge of the roof.	
Roof protection	
All edges of roof boards should be collected after installation with U section	
galvanized profiles from 4 sides to protect edges from rust, the lower long side	
that connects to the gutter should be fixed according to details.	
Electricity network:	
-Sockets and outlets: Supply, Install and Connect 3 pin Single-Phase 16 Amp	
sockets outlet points including (3*2.5mm2) including wires, conduits, sockets,	
draw boxes and all accessories up to DB as per drawings and specifications.	
-Lighting Points: Supply, Install and Connect Lighting Points including Conduits	
and (3*1.5 mm2) Wires up to the DB, Light Switches and all accessories as per	
drawings and specifications.	
-Lighting Fixtures: Supply, Install and Connect surface mounted decorative	
round Ø30cm waterproof lighting fixture 26w PL lamps with metal base and	
milky opal diffuser to the base with four screws IP54 lighting Fixtures including	
Boxes, switches, push buttons), bulbs or tubes. Correction capacitors and all	
accessories as per drawings and specifications.	
-All external wiring works must be XLP cables and applied in plastic truncks with	
suitable dimensions.	
-All according to the specifications, detailed drawings and ACTED supervisor	
engineer instructions.	
Supply and Install a Charged Solar Energy Lamp:	
- Type: Ball Bulbs	
- Output power: 40W	
- Luminous flux: 130LM	
- CCT/Wavelength: 6500K	
- Voltage(V): DC 5V	
- Charging time (by solar panel): 5h	
- Using time: 3h	
- Lifespan: 30000hrs	
- Sheathing material: ABS synthetic plastics	
- Size: Solar panel: 50 x 50 cm.	
Supply and deliver a closed cartoon box of Hygiene Kit :	



	 -Hand Sanitizer (Instant hand sanitizer, approved brand by Palestinian MOH, size 400 MI). -Hand Soap (hypoallergenic, unperfumed, individually wrapped & with far expiry dates). (10 pieces) -Toilet rolls (good quality with soft double-layer tissue that can be used for different purposes) (36 pieces) -Shampoo (1 bottle with 750 ml capacity) -Toothbrush (2 pieces) -Toothpaste (2 pieces, with 150ml) (Colgate type or equivalent). 			
1.b	Residential Block Structure 32 m ² – <u>without Toilet:</u> Ditto, (as mentioned in section 1.a) but excluding the following specification: - Toilet tiles, Toilet, Water tap, Basin, Shower base, Shower tape, 1 Wooden door, 1 Window 60x60	L.S	1	

Residential Block Structure 48 m²

Design code: BS48

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings, and Engineer approval.

This is a quick construction technique, the work in site should be executed maximum within 7 days from receiving the Call-off purchase order.

No.	ltem	Unit	Estimated Quantity	Unit Price in USD Ex. VAT	Total Price in USD EX. VAT
2.a	 Reinforced concrete B-250 floor slabs with ground beams: -Supply, mix and cast reinforced concrete floor slab grade 'B 250' of cement content not less than 300 kg and reinforcement steel (8mm bars every 20cm in both directions. Including the ground beams with their reinforcement steel. -Price to include formwork, reinforcement, installing of plastic sheets between the concrete and the ground, curing and all necessary works. -Do all required excavating and filing in order to obtain levelled ground with zero level slopes under the structures and in the school yard. -Excavation to any depth in any type of soil including rock. -To use selected materials under the structural elements (beams and columns) and school yard. Price to include levelling compacting and watering. -All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Concrete block works: Supply and build concrete block walls, Grade 35 of high quality standards with block dimensions (40x20x15) cm according to the detailed drawings and supervisor engineer instructions; Block works include:- -Vertical and horizontal joints. -Cement and mortar. -Galvanized angles butterfly ties (at joints and between walls with different materials . 	L.S	2		



 -Inites and bond beams to the full length of the walk with minimum height of 20 m and in the same wall thereas of reinforced concrete grade 3-200 with due reinforcement steel, on top of does and windows or as specified per drawings, specifications and supervisor engineer instructions. 			
with due reinforcement steel, on top of doors and windows or as specified per dawings. -All needed materials and work to complete job as per dawings, specifications and supervisor empirer instructions. Internal and external plastering: -Supply and apply internal and external plaster of natural thermal insulation plaster Styrom type (ST* 100 Akk) or equivalent mixed with bega bond. -Thermal Conductivity: 0.048 W(m.K).	-Lintels and bond beams to the full length of the wall with minimum height		
 per drawings. -All needed materials and work to complete job as per drawings, specifications and supervisor engineer instructions. Internal and external plaster of natural thermal insulation plaster styromit type (ST* 100 AABA) or equivalent mixed with hega bond. -Thermat Conductivity: (D48 W), (m, st). -Ratering works should be in two layers, the final one is for fair finish frace. The total plaster theicness should be 10.13 cm. -All according to the specifications, detailed drawings and supervisor engineer instructions. -Stepply and install cali made Scm thick marble frame for all windows' sides, top and botub metallocal made Scm thick marble frame for all windows' sides, top and botub m. -The windows and frames must be prepared before starting the limplementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. -Totie tite: -Supply install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skiriting same type and size, roun tick with same marble, chapping, botaling and jointing in coment and and mortar with rata 13, and 2-3cm thick, pointing with approved materials, required adsays or same supply, install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skiriting same type and size, roun tild by the specifications, detailed drawings and supervisor engineer instructions. -Works to include supply, install and finish on equivalent, [All walls should be the first dura marble polishing and clearing (colors according to supervisor engineer instructions. -Works to include supply, install and finish one (5 cm thick) marble Door threshold. -Works to include supply, install and finish one (5 cm thick) marble Door threshold. -Works to include supply, install and fini	of 20 cm and in the same wall thickness of reinforced concrete grade B-200		
 All needed materials and work to complete job as per drawings, specifications and supervisor engineer instructions. Internal and external plastering: Supply and apply internal and external plaster of natural thermal insulation plaster Stronk should be into wayers, the final one is for fair finish face. The total plaster thickness should be 1.0-1.5 cm. -Pastering work should be intoxulated be 2.0-1.5 cm. -Supply and insult local made Scm thick marble frame for all windows' sides, total plaster thickness float db es the should be a the should be intoxulated frame for all windows' sides, total and be install local made Scm thick marble frame for all windows' sides, total and bettom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Taike window Pice cash Porchain skitling same type and site, 7 run thick marble change page and finish of a cment and samd mortar with ratu 13, and 2-3cm thick, pointing with approved materials, required addshup on samd fill, and on step rinding where required, polishing and dicting in clinic plaster engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (S cm thick) marble Door, the width of limits must be the same as the wall idexip of explored instructions, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (S cm thick) marble Door, the width of limits must be the same as the wall idexip. -Marble Door threshold: -Works to include supply, install and finish one (S cm thick) marble Door, threshold, the width of intens must be the same as the wall depth. -External onef, supprive, install and f	with due reinforcement steel, on top of doors and windows or as specified		
 specifications and supervisor engineer instructions. Internal and external plastering: Supply and neghy internal and external plaster of natural thermal insulation plaster Styronii type (STY 300 KABA) or equivalent mixed with bega bond. -Thermat Conductivity: 0.048 (Wink), -Blatering works should be in two layers, the final one is for fair finah face. The total plaster thickness should be 10.1-15 cm. -All according to the specifications, detailed drawings and supervisor engineer instructions. -Steel angle should be installed in each corner internally and externally. Markhe window frames (Intil): -Supply and install ocal made 5cm thick marble frame for all windows' sides, top and bottom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tole tile: -Supply, install and finish porcelain floor tiles lazer cutting, haf glossy Polith. Price tile: -Supply, install and finish porcelain floor tiles lazer cutting, haf glossy Polith. Price tile: -Supply, install and finish porcelain floor tiles lazer cutting, haf glossy Polith. Price tile: -Supply, and install local making sing may page and size, 7 cm thick marble chapping, beding and joriting incernet and same mortar with ratio 1.3, and 2.3 em thick, painting with approved materials, required adasky or supervisor engineer instructions. -Morts to include supply, unstall and finish two G the theoly marble door, the with With this size 0.9 em, Threw Hindows St. -Foor tile: 20 × 40.9 cm, Threw Hindows St. -Foor tile: 20 × 40.9 cm, Threw Hindows St. -Foor tile: 20 × 40.9 cm, Threw H	per drawings.		
Internal and external plaster of natural thermal insulation plaster Syronic type (STY 160 KAB) or equivalent mixed with bega bond. -Thermal Conductivity: QAB8 W(m.K). -Plastering works should be in too layers; the final one is for fair finish face. The total plaster thickness should be 1.0-1.5 cm. -All according to the specifications, detailed drawings and supervisor engineer instructions. -Steel angle should be installed in each corner internally and externally. Marble window frames (lentils): -Supply and install local made 5cm thick marble frame for all windows' sides, top and bottom. -The windows and frames must be prepared before starting the implementation in site to ensure the quack implementation of the new structures. -All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. -Supply, Install and finich porcelain floor tiles lazer curting, half glossy Polish. Price to include supply, Install and finish two (3 cm thick) marble door, the with fail of 1.2, and 2.3 cm thick, pointing with approved materials, required adsisysh or sand fill, and on site grinding where required, polishing and cleaning, (color starcording to supervisor engineer instructions. -Works to include supply, Install and finish one (5 cm thick) marble door, the with for lines with so do 3 cm, Turkish brand or equivalent, (All walls should be installed by from the grinding where required, polishing and cleaning, (color the sould bottom, detailed drawings and supervisor engineer instructions. -Works to include supply, install and finish one (5 cm thick) marble Door th	-All needed materials and work to complete job as per drawings,		
Supply and apply internal and external plaster of natural thermal insolution plaster Syrond type (ST 160 KAB) or equivalent inside with bega bond. -Thermal Conductivity: 0.048 W/(m, K). -Plastering works should be in too bayers, the final one is for fair finish face. - All according to the specifications, detailed drawings and supervisor engineer instructions. - Steel angle bound be install local made Som thick marble frame for all windows' sides, top and bound. - The windows and frames must be prepared before starting the implementation of the new structures. - Window fames (lentils): - Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. - First to include recased Porcelain sidring same yean alise, Z on thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.3, and 3-and thick, pointing with approved materials, required adskysh or sand fill, and on site grinding where required, polishing and cleaning, (color saccording to supervisor engineer instructions). - Works to include supply, install and finish one (3 cm thick) marble door, the width of intell field withor or equivalent, (Ali walls should be install divide marble drawings and supervisor engineer instructions. - Walls to size: 20x 40x 3: cm, Turkish brand or equivalent, Ali walls should be started with of marble frame (7 ali walls frame), install and finish one (5 cm thick) marble door, the width of intell withor of the work of anise mass the wall the finish frame. - Works to include supply, install and finish one (5 cm thick) marble door, the width of int	specifications and supervisor engineer instructions.		
Supply and apply interial and external plaster of natural thermal insulation plaster Styronic type (STY 160 KAB) or equivalent mide with bage bond. -"Thermal Conductivity: 0.048 W/(m.K). -"Plastering works should be in too layers, the final one is for fair finish face. The total plaster thickness should be in.0.1.5 cm. ->Steel angle bould be installed in each corner internally and externally. Marble window frames (lentils): Supply and install local made 5cm thick marble frame for all windows' sides, top and boutom. -The windows and frames must be prepared before starting the implementation in site to ensare the quack implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. -Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include supply, install and finish two (3 cm thick) marble door, the with rol to 1.3, and 3-om thick, pointing with approved materials, required adskyah or sand fill, and on site grinding where required, polishing and cleaning, (color saccording to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the with of linites must be the same as the wall thicknes. -Will bit list is: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be install of same more of spiners). -Works to include supply, install and finish one (5 cm thick) marble door, the withro finites must be the same as the wall thichnes. -Works to inc			
plaster Styronit type (STY 130 KABA) or equivalent mixed with bega bond. -Thermat Conductivity: 0.044 W(mk), -Plastering works should be in two layers, the final one is for fair finish face. The total jatter thickness should be 1.0-1.5. cm. -All according to the specifications, detailed drawings and supervisor engineer install local made 5cm thick marble frame for all windows' sides, top and bottom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tolet tiles: -Supply and install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include threase at Porcelain skring same type and size, 7 cm thick with same marble chipping. bedding and jointing in cement and said motar datasing, close and thil, and on site grinding where required, polising and clearning, closing, used and on site grinding where required, polising and clearning, closing and a size finding where required, polising and clearning, closing with appoints with appoints with appoints with result in the size and said motar adsaylor os and fill, and on site grinding where required, polising and clearning, closing and a size and said or equivalent. - Works to include supply, install and finish now (5 cm thick) marble door, the with for its: 20 × 40 × 5 cm, Turkish brand or equivalent, - Marbe Door threshold: - Nore its: 100 with specifications, detailed drawings and supervisor engineer instructions. Supply and install "sandwich pamel" baards consist of double galvanized 0.5 m thickness steel sheets, with mixed coord (sliver for external side and with for intreshold: - Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich pamel" baards consist of double galvanized 0.5 m thickn	Internal and external plastering:		
 Thermal Conductivity: 0.048 W/(m.K). Pilastering works should be into Wo layers; the final one is for fair finish face. The total plaster thickness should be 1.0-1.5 cm. All according to the specifications, detailed drawings and supervisor engineer instructions. Steel angle should be installed in each corner internally and externally. Marble window frames (lentit): Supply and install local made Scm thick marble frame for all windows' sides, top and bottom. The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tolet tiles: Supply, Install and finish porcelian floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelian skirting same type and size, 7 cm thick with same marble chipping, bedding and joining in cement and and mortar with ratio 1.3, and -3 cm thick, pointing sime type and size, 7 cm thick with same marble chipping, bedding and joining in cement and size, 7 cm thick with same marble chipping, bedding and pointing and mortar with ratio 1.3, and -3 cm thick, pointing with approved materials, required adsizyh or suffil, and on size priving internet engliced, polishing and cleaning. (colors according to supervisor engineer instructions). Works to include supply, install and finish two equivalent, (All walls should be tiled fully from the ground to rool). Floor tile: 20 x 40 x 9. cm, Turkish brand or equivalent, (All walls should be bloor threshold: Works to include supply, install and finish one (5 cm thick) marble boor threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards' dimensions are (230x17x5) cm, and they are fined with fromes of ug	-Supply and apply internal and external plaster of natural thermal insulation		
Plastering works should be in two layers, the final one is for fair finish face. The total plaster thickness should be 10.9.15 cm. All according to the specifications, detailed drawings and supervisor engineer instructions. Steel angle should be installed in each corner internally and externally. Marche window frames (lentils): Supply and install local made Scm thick martle frame for all windows' sides, top and bottom. The windows and frame must be prepared before starting the implementation in site to ensure the quck implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tolet tile: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Percensin skrifting same type and size, 7 on thick with ratio 1.3, and 3-5m thick, pointing with approved materials, call carrier, 1, and 3-5m thick, pointing with approved materials, supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include supply, install and finish two (3 on thick) marble door, the with ratio 1.3, and 3-5m thicks brand or equivalent, (All walls should be tild of 10 into the ground to rood, -floor tile: 20 × 40 × 2 m, Turkich brand or equivalent, -floor tile: 20 × 40 × 2 m, Turkich brand or equivalent, -floor tile: 20 × 40 × 2 m, Turkich brand or equivalent, -floor tile: 20 × 40 × 2 m, Turkich brand regions and supervisor engineer instructions. External roof: Supply and install "sandwich panel" boards' consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and White for interal lone, paperadic steel angle (Tor x 7 m x 7 m x Tor) with thickness of 3mm from all sides, All fined by special screws and elas	plaster Styronit type (STY 160 KABA) or equivalent mixed with bega bond.		
The total plaster thickness should be 1.0-1.5 cm. All according to the specifications, detailed drawings and supervisor engineer instructions. -Steel angle should be installed in each corner internally and externally. Marbie window frames (leutis): -Supply and install local made Scm thick marble frame for all windows' sides, top and botom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tolet tiles: -Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cernent and and motrar with ratio 1.3, and 2-3 cm thick, pointing sime type and size, 7 cm thick with same marble chipping, bedding and jointing in cernent and and motrar with ratio 1.3, and 2-3 cm thick, pointing with approved materials, required adasiyah or supervisor engineer instructions). -Works to include supply, install and finish two c quivalent, (All walls should be tiled fully from the ground to rool). -Floor tile: 20x 40x 9. cm, Turkish brand or equivalent, (All walls should be to include supply, install and finish two (5 cm thick) marble door, the width of lintels must be same as the wall depth. External roof: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one, separated by 7 cm of righ density Polytyrene (Kalkal) with 120 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with finenes of U galvanized steel angle (7 cm x 7 cm x 7 cm X run) with thickness of 3mm from	-Thermal Conductivity: 0,048 W/(m.K).		
-All according to the specifications, detailed drawings and supervisor engineer instructions. -Steel angle should be installed in each corner internally and externally. Marble window frames (lentils): -Supply and install local made Scm thick marble frame for all windows' sides, top and bottom. -The windows and frame smust be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tollet tile: -Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Frecast Percentian Skriting same type and size, zor m tick. with ratio 13, and 3-26m thick, pointing with sproved materials, required adasish or sand fill, and on site grinding where required, polishing and desting. (close according to supervisor engineer instructions). -Works to include supply, install and finish two (2 m thick) marble door, the with fail to 18 and 30 s 0 m. Turkish brand or equivalent, (All walls shuld be tild (ully from the ground requivalent, equivalent and the specifications, detailed drawings and supervisor engineer instructions). Marble Door threshold:	-Plastering works should be in two layers, the final one is for fair finish face.		
 engineer instructions. Steel angle should be installed in each corner internally and externally. Marble window frames (lentils): Supply and install local made 5cm thick marble frame for all windows' sides, top and bottom. The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tollet tile: Supply. Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Prire to include Pre-cast Porcelain skirling same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 13, and 2-3cm thick, pointing with approved materials, required adasiysh or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). Works to include supply, install and finish two (3 cm thick) marble door, the witht of intels must be ame as the wall thickness. Walls tile size: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be tild furf must be ground to roof). Floor tile: 20 x 40 x 3 cm, Turkish brand or equivalent, All walls should be tild furf to the ground to roof). Horks to include supply, install and finish one (5 cm thick) marble Door threshold: Works to include supply, install and finish one (5 cm thick) marble Door threshold. External roof. Supply and install "sodowich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (supercisions) general angle (7 cm x 7 cm x 7 cm) with thickness of am from all sides. All fixed by special screws and elaster they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of am from all sides. All fixed by special screws and elaster to prevent water leakape according to the de	The total plaster thickness should be 1.0-1.5 cm.		
- Steel angle should be installed in each corner internally and externally. Marble vindows fames (lentils): - Supply and install local made Scor thick marble frame for all windows' sides, top and bottom The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tollet tiles: - Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skiting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah or san fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions) Works to include supply, install and finish two (3 cm thick) marble door, the width of linetis must be same as the wall thickness Walls ties: 20 x 40 x 9 cm. Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof) Floor the: 20 x 40 x 9 cm. Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof) Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (2 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door threshold; - Works to include supply, install and finish one (5 cm thick) marble Door thre	-All according to the specifications, detailed drawings and supervisor		
Marble window frames (lentils): -Supply and install local made Scm thick marble frame for all windows' sides, top and bottom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tollet tile: -Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skring same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 13. and 2-3cm thick, pointing with approved materials, required adasiyah or samd fill, and on site grinding where required, polishing and cleaning, cloors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the witht of intels must be asme as the wall thickness. -Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tile fully from the ground to roci). -Harcotoff -Works to include supply, install and finish one (5 cm thick) marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External cooff Supply and install "Sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed coor (silve) for portars and side and white for internal one), separated by 7 cm of high density Polystyrene (Salvanized steel Lineshoff and linesh. All accord	engineer instructions.		
 Supply and install local made Som thick marble frame for all windows' sides, top and bottom. The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tiles: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 13, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning (colors according to supervisor engineer instructions). Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hoor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hoor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Hor tile: Source and the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: Yor to include supply, install and finish toe (5 cm thick) marble Door threshold, the width of intels must be the same as the wall depth. External roof! <li< td=""><td>-Steel angle should be installed in each corner internally and externally.</td><td></td><td></td></li<>	-Steel angle should be installed in each corner internally and externally.		
 Supply and install local made Scm thick marble frame for all windows' sides, top and bottom. The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tiles: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.3, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning (colors according to supervisor engineer instructions.) Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. Walls ties 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to rool). Floor tie: 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to rool). Hort tie: 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to rool). Hort tie: 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to rool). Hort tie: 20 x 40 x .9 cm, Turkish trand or equivalent, (All walls should be tiled fully from the ground to rool). Hort tie: 20 x 40 x .9 cm, Turkish trand or equivalent, (All walls should be tiled fully from the ground to rool). Hort tie: 20 x 40 x .9 cm, Turkish trand or equivalent, (All walls should be tiled fully from the ground to rool). Fort tie: 20 x 40 x .9 cm, Turkish trand or equivalent, (All walls the tilt to rool). Supply and install metal bac			
 top and bottom. The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Tollet tiles: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and piniting in cement and sand mortar with ratio 1.3, and 2.3-cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of linels must be asme as the wall thickness. -Walls tile size: 20 x 40 x. 9 cm, Turkish brand or equivalent, (All walls should be tilef fully from the ground to roof). -Floor tile: 20 x 40 x. 9 cm, Turkish brand or equivalent, (All walls should be tilef fully from the ground to roof). -Hoor tile: 20 x 40 x. 9 cm, Turkish brand or equivalent, (All walls should be tilef fully from the ground to roof). -Works to include supply, install and finish one (5 cm thick) marble Door threshold; -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. Etermal roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and with for internal one), separated by 7 cm or 1/0 high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm x 7 cm x 7 cm x 1 cm) with hinchess of 3 mm rom all sides. All fixed by special screw	Marble window frames (lentils):		
 The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tile: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 13, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and deaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness ate = sheets, with mixed color (silver for external side and white for internal one), separated by 2 cm of high density Polystyrene (Kalkal) with E20 of compression. The board's dimensions are (20x117x) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 1 flox dues galvanized is crews and elastic rubber to prevent water leakage according to the detailed drawings. Beard weight must be at least 10 kg/sqn. Galvanized profiles as indicated below: Supply and install acconding (8 x 8) cm, and 2mm thick, which has to be installed inside the board seam (8 x 4), and 2mm thick which has to be m	-Supply and install local made 5cm thick marble frame for all windows' sides,		
 Implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tiles: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.3, and 2.3cm thick, pointing in cement and sand mortar with ratio 1.3, and 2.3cm thick pointing in cement and sand mortar with ratio 1.3, and 2.3cm thick pointing in their required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. -Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tile fully from the ground to roof). -Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tile fully from the ground to roof). -Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tile fully from the ground to roof). -Works to include supply, install and finish one (5 cm thick) marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold; Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), separated by 7 cm or high density Polytyprene (Kalka) with F20 of compression. The boards' dimensions are (230x117z6) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm x 7 cm x 7 cm x) cm, and thickness of amm from all sides. All fixed by special screws and	top and bottom.		
structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tiles: -Supply, Install and finish porcelain skrifting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.33, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of linitelis must be same as the wall thickness. -Walls tiles is: 20 x 40 x 9. cm. Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Floor tile: 20 x 40 x 9. cm. Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of linitels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), espearted by 7 cm or high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230cL17x5) cm, and thy are fixed with frames of U galvanized teel apple (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sm. Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install and columes (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), weledel together and fixed correctly on the top (root 516) of the gathered inc boards for each fix	-The windows and frames must be prepared before starting the		
All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Toilet tiles: Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chiping, bedding and jointing in cement and sand mortar with ratio 1.3, and 2-3 cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. -Walls tile size: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Floor tile: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Floor tile: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Floor tile: 20 x 40 x 3 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Works to include supply, install and finish one (5 cm thick) marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble door, the with which finiters is unde show and the damaing and (2117x5) (Cm, and they are fload with threase 0 (Silve for external side and white for internal one), separated by 7 cm of high density Polystyrene ((Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) (Cm, and they are fload with threase 0 (Sin Manized steell angle (7 cm x 7 cm x 7 cm) with thickness	implementation in site to ensure the quick implementation of the new		
engineer instructions. Toilet tiles: -Supply, Instail and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.3, and 2-3 cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions)Works to include supply, install and finish two (3 cm thick) marble door, the with of lintels must be same as the wall thicknessWalls tile size: 20 x 40 x - 9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to reof)Floor tile: 20 x 40 x - 9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm or high density Polystyrene ((Kalkai) with F20 of compression. The boards' dimensions are (E30x117x5) cm, and they are fixed with frames of U galvanized to Equivalent, they are fixed with frames of U galvanized to Equivalent the edile drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install on column (8 x 8) cm, and 2mm thick. As indicated in the drawing Galvanized steel L angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered sire charded,	structures.		
engineer instructions. Toilet tiles: -Supply, Instail and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1.3, and 2-3 cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions)Works to include supply, install and finish two (3 cm thick) marble door, the with of lintels must be same as the wall thicknessWalls tile size: 20 x 40 x - 9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to reof)Floor tile: 20 x 40 x - 9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm or high density Polystyrene ((Kalkai) with F20 of compression. The boards' dimensions are (E30x117x5) cm, and they are fixed with frames of U galvanized to Equivalent, they are fixed with frames of U galvanized to Equivalent the edile drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install on column (8 x 8) cm, and 2mm thick. As indicated in the drawing Galvanized steel L angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered sire charded,	All according to the specifications, detailed drawings and ACTED supervisor		
-Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain floor tiles lazer cutting, half glossy Polish. With same marble chipping, bedding and jointig in cement and sand mortar with ratio 1:3, and 2:3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. - Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). - Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold; the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastir tube to a least to tall the divery separated profi			
-Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain floor tiles lazer cutting, half glossy Polish. With same marble chipping, bedding and jointig in cement and sand mortar with ratio 1:3, and 2:3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. - Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). - Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold; the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastir tube to a least to tall the divery separated profi			
Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. -Walls tile size: 20x 40 x.9 cm, Turkish brand or equivalent, -Haccording to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalka) with F20 of compresion. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of amm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the d	Toilet tiles:		
with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning, (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. - Walls tile size : 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to rool). - Floor tile : 20 x 40 x.9 cm, Turkish brand or equivalent, - All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) xif thickness steel sheets, with we shell seets. All show to yspecial screws and elastic rubber to prevent water leakage according to the detai	-Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish.		
with ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the witht of lintels must be same as the wall thickness. - Walls tite isze: 20 × 40 × 9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). - Floor tite: 20 × 40 × 9 cm, Turkish brand or equivalent, (All walls carding to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "samdwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. </td <td>Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick</td> <td></td> <td></td>	Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick		
adasiyah or sand fill, and on site grinding where required, polishing and cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. - Walls tile size : 20 x 40 x. 9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). - Floor tile : 20 x 40 x. 9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polyterene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x) r m) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Balvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawings. <t< td=""><td>with same marble chipping, bedding and jointing in cement and sand mortar</td><td></td><td></td></t<>	with same marble chipping, bedding and jointing in cement and sand mortar		
cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. • Walls tile size: 120 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). - Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bord beam as indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside	with ratio 1:3, and 2-3cm thick, pointing with approved materials, required		
-Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. -Walls tile size: 20: 40: 8.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). -Floor tile: 20: 40: 8.9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elasticr tubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated together and fixed correctly on the top (roof side) of the gathered zinc boards fore acch facade,	adasiyah or sand fill, and on site grinding where required, polishing and		
width of lintels must be same as the wall thickness. • Walls tile size: 20 x 40 x.9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). • Floor tile: 20 x 40 x.9 cm, Turkish brand or equivalent, • All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: • Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3 mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bom beam as indicated in the drawings. • Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered inc	cleaning. (colors according to supervisor engineer instructions).		
 Walls tile size : 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Floor thie: 20 x 40 x .9 cm, Turkish brand or equivalent, All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (sliver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Galvanized steel U angles (1.5mm thick), welde together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 	-Works to include supply, install and finish two (3 cm thick) marble door, the		
should be tiled fully from the ground to roof). - Floor tile : 20 x 40 x. 9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards f	width of lintels must be same as the wall thickness.		
 Floor tile : 20 x 40 x .9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 	- Walls tile size : 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls		
-All according to the specifications, detailed drawings and supervisor engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x r cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	should be tiled fully from the ground to roof).		
engineer instructions. Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3 mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. -Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	- Floor tile : 20 x 40 x .9 cm, Turkish brand or equivalent,		
Marble Door threshold: -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized Justel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	-All according to the specifications, detailed drawings and supervisor		
 -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed install a connected steel beam (8 x 4), and 2mm thick which has to be installed install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 	engineer instructions.		
 -Works to include supply, install and finish one (5 cm thick) marble Door threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed install a connected steel beam (8 x 4), and 2mm thick which has to be installed install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawing. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	Marble Door threshold:		
threshold, the width of lintels must be the same as the wall depth. External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install a connected steel beam (8 x 4), and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression. The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	-Works to include supply, install and finish one (5 cm thick) marble Door		
Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm.	threshold, the width of lintels must be the same as the wall depth.		
Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm.			
 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
 white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
 (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
 cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
 elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade, 			
Board weight must be at least 10 kg/sqm. Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
Galvanized profiles as indicated below: Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	Board weight must be at least 10 kg/sqm.		
Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
Supply and install one column (8 x 8) cm, and 2mm thick. As indicated in the drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
drawing. Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	•		
Supply and install a connected steel beam (8 x 4), and 2mm thick which has to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
to be installed inside the bond beam as indicated in the drawings. - Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,	5		
- Galvanized steel U angles (1.5mm thick), welded together and fixed correctly on the top (roof side) of the gathered zinc boards for each facade,			
correctly on the top (roof side) of the gathered zinc boards for each facade,			
and same for all internal partitions and where needed.			
	and same for all internal partitions and where needed.		



System fixation

It will be pre-prepared, using the CO2 method welding in lines. For the profiles and U angle intersections, welding should be done at the site only when needed; taking into consideration the unit should consist of several complete parts to be joined at the site either by specified welding method or using drilling with 8 mm diameter screws.

Off-white Aluminum windows

-4 Windows (120 x 120) cm, model No.7700 of national industry, and of 4 mm thickness double glass framed by Aluminum profile with a movable galvanized steel external mosquito netting on the whole window.(Three portions).

-2 Window (60 x 60) cm, model No.4000 of national industry, and of 4 mm thickness (Mobazzar) glass framed by Aluminum profile with a movable galvanized steel external mosquito netting on the whole window.(Three portions).

Windows Protections

Supply and implement spear shaped protection for every window in shelter unit, where the protection steel is to be painted with three coats (one primer coat) with the color approved by the Supervisor Engineer. Steel bars; dimensions 10 mm with spacing distance of 12 cm between spears.

Wooden doors (90x200x5)cm

Supply and install 2 wooden doors with the following specifications: - The door shall be made from sandwich boards 17 mm in both sides consisting of pinewood strips placed end to end. The width of each strip shall not exceed 25 mm. The strips shall be placed side by side, which shall then be glued between the two wooden layers from each side (Sandwich and beech layers).

- The surface shall be made with Formica sheets.

- Frames shall be made from Swedish wood with square and flat shape, the corners of frame being fabricated to a true right angle. Both the fixed and opening frames shall be constructed of sections which have been cut to length, mitered and screwed at the corners.

- Good quality of door handle attached with lever lock operated by key and lockable from both inside and outside

Steel Door (100x200x5)cm

Supply and install a steel door with the following details:

- The door shall be made from Galvanized steel sheets 2 mm in both sides consisting (Internal and external), in addition to two steel frames from outside.

- The surface shall be painted twice (Primer layer and grey color)

- Frames shall be manufactured out of (2 mm) Galvanized Steel box 6x3 cm.
- Good quality of door handle attached with lever lock operated by key and lockable from both inside and outside

Toilet

Turkish or European (Based on request)

Turkish toilet: (45*55) cm, caramel color correctly connected to plastic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent. OR

European Water toilet Caramel color correctly connected to ceramic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent.

Water tap

Water tap of type Chrome (long neck) of first grade (Italian or equivalent), which installed on the basin itself.

Basin

Caramel Basin (45*55) cm of type Italian brand or equivalent.



	Shower base		
	Shower base fabricated from metal sheet coated with PVC layer with a clear		
1	esulted area of (80*120) cm, 2mm thickness fixed on steel base with		
5	pecifications as shown in the attached drawings, (see detail BS48).		
(Shower room should be elevated with 20 cm, from the shelter level)		
	Shower tape		
	Single chrome tap with double use (tape and shower hand) of first grade		
(Italian or equivalent),		
	Piping		
	Connecting 2" PVC pipes and needed fitting with suitable length for the		
	hower and kitchen for the purpose of drainage, and 16 mm diameter HDPE		
	pipes for water supplying. The contractor should supply and install buried		
	drilled barrel for drainage.		
	Connecting 4" PVC corrugated HDPE pipes and needed fitting with 10 meter		
	ength as sewer connection.		
	Complements of Charl Charl for Materia (Charles the stars to posse)		
	Supply galvanized Steel Stand for Water tank (See the drawings BS48)		
	Supply transfer, and install polyethylene water tank Size 1 m3:		
	The Water Tank must be made by blow molding method.		
	The water tank must be free of any holes.		
	Water Tank must be made of LLDPE materials in White color.		
	Water tank must have 7 internal rings at least with 1 cm depth for each		
	ing. Water Tank Durability 30 years at least.		
	Water Tank wall thickness must not be less than (7) mm, with four layers of		
	polyethylene, (White: 2.8 mm, Black: 1.4 mm, Red: 1.4 mm, Blue: 1.4		
	nm).color must be White. The water tank must be free of any holes.		
·			
	Connect the structure (Including toilet and kitchen) and the mobile latrine		
	with the above-mentioned water tank using HDPE pipes up to 12m		
	ong(depends on the real distance in each case) Installing and connecting		
	he system should be implemented correctly to have the system operating.		
	, , , , , , , ,		
-	Supply and install water collectors with include XLPE Pipe 16mm, oven		
1	painted aluminum cabinet with two doors, valves for branches, main valves,		
`	vents, and all accessories.		
	nstallation of 120 cm long kitchen unit.		
	Stainless Steel basin 120 cm, and sandwich wooden cabinets, with Italian		
-	oints or equivalent as shown in the drawings, a good quality cabinet hand,		
	ingle Chrome long neck tap of first grade (Italian or equivalent) fixed to the		
	pasin, and connecting the required water supplying plastic pipes (20 mm		
0	liameter), and 2" PVC sewage pipe connected to the sewer tank.		
	Doof water gutter		
	Roof water gutter Supply and install roof gutter at lowest edge of the roof.		
	אראיין אייא אויזינאוי ויסטי בעננכי מנ וטייבזי בעבר טו נווב וטטו.		
1	Roof protection		
	All edges of roof boards should be collected after installation with U section		
	galvanized profiles from 4 sides to protect edges from rust , the lower long		
	ide that connects to the gutter should be fixed according to details.		
	-		
	Electricity network:		
	Sockets and outlets: Supply, Install and Connect 3 pin Single-Phase 16 Amp		
	ockets outlet points including (3*2.5mm2) including wires, conduits,		
	ockets, draw boxes and all accessories up to DB as per drawings and		
	pecifications.		
	Lighting Points: Supply, Install and Connect Lighting Points including		
	Conduits and (3*1.5 mm2) Wires up to the DB, Light Switches and all		
i	accessories as per drawings and specifications.		



	 -Lighting Fixtures: Supply, Install and Connect surface mounted decorative round Ø30cm waterproof lighting fixture 26w PL lamps with metal base and milky opal diffuser to the base with four screws IP54 lighting Fixtures including Boxes, switches, push buttons), bulbs or tubes. Correction capacitors and all accessories as per drawings and specifications. -All external wiring works must be XLP cables and applied in plastic truncks with suitable dimensions. -All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. 			
	Supply and Install a Charged Solar Energy Lamp : - Type: Ball Bulbs - Output power: 40W - Luminous flux: 130LM - CCT/Wavelength: 6500K - Voltage(V): DC 5V - Charging time (by solar panel): 5h - Using time: 3h - Lifespan: 30000hrs - Sheathing material: ABS synthetic plastics - Size: Solar panel: 50 x 50 cm. Supply and deliver a closed cartoon box of Hygiene Kit :			
	 -Hand Sanitizer (Instant hand sanitizer, approved brand by Palestinian MOH, size 400 MI). -Hand Soap (hypoallergenic, unperfumed, individually wrapped & with far expiry dates). (10 pieces) -Toilet rolls (good quality with soft double-layer tissue that can be used for different purposes) (36 pieces) -Shampoo (1 bottle with 750 ml capacity) -Toothbrush (2 pieces) -Toothpaste (2 pieces, with 150ml) (Colgate type or equivalent). 			
2.b	Residential Block Structure 48 m ² – <u>without Toilet:</u> Ditto, (as mentioned in section 2.a) but excluding the following specification: - Toilet tiles, Toilet, Water tap, Basin, Shower base, Shower tape, 1 Wooden door, 1 Window 60x60	L.S	1	



Fixed Latrine

Design code: FL

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

This is a quick construction technique, the work in site should be executed maximum in within 7 days from receiving the Call-off purchase order.

No.	ltem	Unit	Estimated Quantity	Unit Price in USD Ex. VAT	Total Price in USD EX. VAT
3	 Reinforced concrete B-250 floor slabs with ground beams: -Supply, mix and cast reinforced concrete floor slab grade 'B 250' of cement content not less than 300 kg and reinforcement steel (8mm bars every 20cm in both directions. Including the ground beams with their reinforcement steel. -Price to include formwork, reinforcement, installing of plastic sheets between the concrete and the ground, curing and all necessary works. -Do all required excavating and filing in order to obtain levelled ground with zero level slopes under the structures and in the school yard. -Excavation to any depth in any type of soil including rock. -To use selected materials under the structural elements (beams and columns) and school yard. Price to include levelling compacting and watering. -All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Concrete block works: Supply and build concrete block walls, Grade 35 of high quality standards with block dimensions (40x20x15) cm according to the detailed drawings and supervisor engineer instructions; Block works include: -Vertical and horizontal joints. -Cement and mortar. -Galvanized angles butterfly ties (at joints and between walls with different materials. -Lintels and bond beams to the full length of the wall with minimum height of 20 cm and in the same wall thickness of reinforced concrete grade B-200 with due reinforcement steel, on top of doors and windows or as specifications and supervisor engineer instructions. Internal and external plastering: -Supply and apply internal and external plaster of natural thermal insulation plaster Styronit type (STY 160 KABA) or equivalent mixed with bega bond. -Thermal Conductivity: 0,048 W/(m.K). -Plastering works should be in two layers, the final one is for fair finish face. The total plaster thickness should be in 0.0-1.5 cm. -All according	L.S	2		
I	and bottom.				



-	-The windows and frames must be prepared before starting the implementation			
	in site to ensure the quick implementation of the new structures.			
	All according to the specifications, detailed drawings and ACTED supervisor			
	engineer instructions.			
	Tiles:			
	-Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish.			
	Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with			
	same marble chipping, bedding and jointing in cement and sand mortar with			
	ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah			
	or sand fill, and on site grinding where required, polishing and cleaning. (colors			
	according to supervisor engineer instructions).			
	-Works to include supply, install and finish two (3 cm thick) marble door, the			
	width of lintels must be same as the wall thickness.			
	- Walls tile size : 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be			
	tiled fully from the ground to roof).			
	 Floor tile : 20 x 40 x .9 cm, Turkish brand or equivalent, 			
	-All according to the specifications, detailed drawings and supervisor engineer			
	instructions.			
	External roof:			
	Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm			
	thickness steel sheets, with mixed color (silver for external side and white for			
	internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of			
	compression .The boards' dimensions are (230x117x5) cm, and they are fixed			
	with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of			
	3mm from all sides. All fixed by special screws and elastic rubber to prevent			
	water leakage according to the detailed drawings. Board weight must be at least			
	10 kg/sqm.			
	-1Window (60 x 60) cm, model No.4000 of national industry, and of 4 mm			
	thickness (Mobazzar) glass framed by Aluminum profile with a movable			
	galvanized steel external mosquito netting on the whole window.(Three			
	portions).			
	Steel Door (100x200x5)cm			
	Supply and install a steel door with the following details:			
	- The door shall be made from Galvanized steel sheets 2 mm in both sides			
	consisting (Internal and external), in addition to two steel frames from outside.			
	- The surface shall be painted twice (Primer layer and grey color)			
	- Frames shall be manufactured out of (2 mm) Galvanized Steel box 6x3 cm.			
	 Good quality of door handle attached with lever lock operated by key and 			
	lockable from both inside and outside			
	Toilet			
	Turkish or European (Based on request)			
	Turkish toilet: (45*55) cm, caramel color correctly connected to plastic flush tank			
	(Negara 3/6 litters with buttons on top) Italian brand or equivalent.			
	<u>OR</u> European Water toilet Caramel color correctly connected to ceramic flush tank			
	(Negara 3/6 litters with buttons on top) Italian brand or equivalent.			
	incours of o inters with buttons on topy italian brand of equivalent.			
	Water tap			
	Water tap Water tap of type Chrome (long neck) of first grade (Italian or equivalent), which			
	installed on the basin itself.			
	Hand Water Spray of type Italian brand or equivalent.			
	Basin			
	Caramel Basin (45*55) cm of type Italian brand or equivalent.			
	Shower base		 	
_				



Shower base fabricated from metal sheet coated with PVC layer with a clear	
resulted area of (80*120) cm, 2mm thickness fixed on steel base with	
specifications as shown in the attached drawings, (see detail FL).	
······	
Shower tape	
Single chrome tap with double use (tape and shower hand) of first grade (Italian	
or equivalent),	
Piping	
- Connecting 2" PVC pipes and needed fitting with suitable length for the shower	
and kitchen for the purpose of drainage, and 16 mm diameter HDPE pipes for	
water supplying. The contractor should supply and install buried drilled barrel for	
drainage.	
-Connecting 4" PVC corrugated HDPE pipes and needed fitting with 10 meter	
length as sewer connection.	
- Supply galvanized Steel Stand for Water tank(See the drawings FL)	
- Supply transfer, and install polyethylene water tank Size 1 m3:	
-The Water Tank must be made by blow molding method.	
-The water tank must be free of any holes.	
-Water Tank must be made of LLDPE materials in White color.	
-Water tank must have 7 internal rings at least with 1 cm depth for each ring.	
-Water Tank Durability 30 years at least.	
-Water Tank wall thickness must not be less than (7) mm, with four layers of	
polyethylene, (White: 2.8 mm, Black: 1.4 mm, Red: 1.4 mm, Blue: 1.4 mm).	
- color must be White.	
- The water tank must be free of any holes	
-Supply and install water collectors with include XLPE Pipe 16mm, oven painted	
aluminum cabinet with two doors, valves for branches, main valves, vents, and	
all accessories.	
Supply and Install a Charged Solar Energy Lamp :	
- Type: Ball Bulbs	
- Output power: 40W	
- Luminous flux: 130LM	
- CCT/Wavelength: 6500K	
- Voltage(V): DC 5V	
- Charging time (by solar panel): 5h	
- Using time: 3h	
- Lifespan: 30000hrs	
- Sheathing material: ABS synthetic plastics	
- Size: Solar panel: 50 x 50 cm.	
Supply and deliver a closed cartoon box of Hygiene Kit :	
-Hand Sanitizer (Instant hand sanitizer, approved brand by Palestinian MOH, size 400 MI).	
-Hand Soap (hypoallergenic, unperfumed, individually wrapped & with far expiry dates).	
(10 pieces)	
-Toilet rolls (good quality with soft double-layer tissue that can be used for different	
purposes) (36 pieces)	
-Shampoo (1 bottle with 750 ml capacity)	
-Toothbrush (2 pieces)	
-Toothpaste (2 pieces, with 150ml) (Colgate type or equivalent).	



Fixed Latrine

Design code: FL

Price includes wages, material, accessories, supplying, fabrications, installation, and fixation in the desired location for every unit, where all materials must be of (TAKEN quality) or equivalent, or as specified type or class. The contractor should prepare a complete shelter unit, fully detailed to be approved by the Engineer and considered as a sample, before fabricating the remaining units. All material should match the specifications, detailed drawings and Engineer approval.

This is a quick construction technique, the work in site should be executed maximum in within 7 days from receiving the Call-off purchase order.

No.	Item	Unit	Estimated Quantity	Unit Price in USD EX. VAT	Total Price in USD EX. VAT
3	 Reinforced concrete B-250 floor slabs with ground beams: Supply, mix and cast reinforced concrete floor slab grade 'B 250' of cement content not less than 300 kg and reinforcement steel (8mm bars every 20cm in both directions. Including the ground beams with their reinforcement steel. Price to include formwork, reinforcement, installing of plastic sheets between the concrete and the ground, curing and all necessary works. Do all required excavating and filing in order to obtain levelled ground with zero level slopes under the structures and in the school yard. Excavation to any depth in any type of soil including rock. To use selected materials under the structural elements (beams and columns) and school yard. Price to include levelling compacting and watering. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions. Concrete block works: Supply and build concrete block walls, Grade 35 of high quality standards with block dimensions (40x20x15) cm according to the detailed drawings and supervisor engineer instructions; Block works include:- Vertical and horizontal joints. Cement and mortar. Galvanized angles butterfly ties (at joints and between walls with different materials. Lintels and bond beams to the full length of the wall with minimum height of 20 cm and in the same wall thickness of reinforced concrete grade B-200 with due reinforcement steel, on top of doors and windows or as specified per drawings. All needed materials and work to complete job as per drawings, specifications and supervisor engineer instructions. Internal and external plastering: Supply and apply internal and external plaster of natural thermal insulation plaster Styronit type (STY 160 KABA) or equivalent mixed with bega bond. Thermal Conductivity: 0,048 W/(m.K). Plastering works should be in two layers, the fin	L.S	2		



	1	r	 n
Marble window frames (lentils): -Supply and install local made 5cm thick marble frame for all windows' sides, top and bottom. -The windows and frames must be prepared before starting the implementation in site to ensure the quick implementation of the new structures. All according to the specifications, detailed drawings and ACTED supervisor engineer instructions.			
 Tiles: -Supply, Install and finish porcelain floor tiles lazer cutting, half glossy Polish. Price to include Pre-cast Porcelain skirting same type and size, 7 cm thick with same marble chipping, bedding and jointing in cement and sand mortar with ratio 1:3, and 2-3cm thick, pointing with approved materials, required adasiyah or sand fill, and on site grinding where required, polishing and cleaning. (colors according to supervisor engineer instructions). -Works to include supply, install and finish two (3 cm thick) marble door, the width of lintels must be same as the wall thickness. Walls tile size : 20 x 40 x .9 cm, Turkish brand or equivalent, (All walls should be tiled fully from the ground to roof). Floor tile : 20 x 40 x .9 cm, Turkish brand or equivalent, -All according to the specifications, detailed drawings and supervisor engineer instructions. 			
External roof: Supply and install "sandwich panel" boards consist of double galvanized 0.5 mm thickness steel sheets, with mixed color (silver for external side and white for internal one), separated by 7 cm of high density Polystyrene (Kalkal) with F20 of compression .The boards' dimensions are (230x117x5) cm, and they are fixed with frames of U galvanized steel angle (7 cm x 7 cm x 7 cm) with thickness of 3mm from all sides. All fixed by special screws and elastic rubber to prevent water leakage according to the detailed drawings. Board weight must be at least 10 kg/sqm.			
-1Window (60 x 60) cm, model No.4000 of national industry, and of 4 mm thickness (Mobazzar) glass framed by Aluminum profile with a movable galvanized steel external mosquito netting on the whole window.(Three portions).			
 Steel Door (100x200x5)cm Supply and install a steel door with the following details: The door shall be made from Galvanized steel sheets 2 mm in both sides consisting (Internal and external), in addition to two steel frames from outside. The surface shall be painted twice (Primer layer and grey color) Frames shall be manufactured out of (2 mm) Galvanized Steel box 6x3 cm. Good quality of door handle attached with lever lock operated by key and lockable from both inside and outside 			
Toilet <u>Turkish or European</u> (Based on request) Turkish toilet: (45*55) cm, caramel color correctly connected to plastic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent. <u>OR</u> European Water toilet Caramel color correctly connected to ceramic flush tank (Negara 3/6 litters with buttons on top) Italian brand or equivalent.			
Water tap Water tap of type Chrome (long neck) of first grade (Italian or equivalent), which installed on the basin itself.			
Hand Water Spray of type Italian brand or equivalent.			
Basin			



Caramel Basin (45*55) cm of type Italian brand or equivalent.		
Channes have		
Shower base Shower base fabricated from metal sheet coated with PVC layer with a clear		
resulted area of (80*120) cm, 2mm thickness fixed on steel base with		
specifications as shown in the attached drawings, (see detail FL).		
specifications as shown in the attached arawings, (see detail 12).		
Shower tape		
Single chrome tap with double use (tape and shower hand) of first grade		
(Italian or equivalent),		
Piping		
 Connecting 2" PVC pipes and needed fitting with suitable length for the shower and kitchen for the purpose of drainage, and 16 mm diameter HDPE 		
pipes for water supplying. The contractor should supply and install buried		
drilled barrel for drainage.		
-Connecting 4" PVC corrugated HDPE pipes and needed fitting with 10 meter		
length as sewer connection.		
- Supply galvanized Steel Stand for Water tank(See the drawings FL)		
- Supply transfer, and install polyethylene water tank Size 1 m3:		
-The Water Tank must be made by blow molding method.		
-The water tank must be free of any holes.		
-Water Tank must be made of LLDPE materials in White color.		
-Water tank must have 7 internal rings at least with 1 cm depth for each ring.		
-Water Tank Durability 30 years at least. -Water Tank wall thickness must not be less than (7) mm, with four layers of		
polyethylene, (White: 2.8 mm, Black: 1.4 mm, Red: 1.4 mm, Blue: 1.4 mm).		
- color must be White.		
- The water tank must be free of any holes		
-Supply and install water collectors with include XLPE Pipe 16mm, oven painted		
aluminum cabinet with two doors, valves for branches, main valves, vents, and		
all accessories.		
Supply and Install a Charged Solar Energy Lamp :		
- Type: Ball Bulbs		
- Output power: 40W		
- Luminous flux: 130LM		
- CCT/Wavelength: 6500K		
- Voltage(V): DC 5V		
- Charging time (by solar panel): 5h		
- Using time: 3h		
- Lifespan: 30000hrs		
- Sheathing material: ABS synthetic plastics - Size: Solar panel: 50 x 50 cm.		
Supply and deliver a closed cartoon box of Hygiene Kit :		
-Hand Sanitizer (Instant hand sanitizer, approved brand by Palestinian MOH, size 400		
MI).		
-Hand Soap (hypoallergenic, unperfumed, individually wrapped & with far expiry dates). (10 pieces)		
-Toilet rolls (good quality with soft double-layer tissue that can be used for different		
purposes) (36 pieces)		
-Shampoo (1 bottle with 750 ml capacity)		
-Toothbrush (2 pieces)		
-Toothpaste (2 pieces, with 150ml) (Colgate type or equivalent).		



BIDDER'S REMARKS:

No.	List of Items	UNIT Price in USD Excluding VAT
1.a	Residential Block Structure 32 m2-With Toilet	
1.b	Residential Block Structure 32 m2 – without Toilet	
2.a	Residential Block Structure 48 m2-With Toilet	
2.b	Residential Block Structure 48 m2 – without Toilet	
3	Fixed Latrine	
4	Fixed PWD Latrine	
	TOTAL Price in USD Excluding VAT	

2.

PLEASE FILL THE BELOW TABLE PER ITEM PER 1 PCS



GENERAL CONDITIONS OF PURCHASE

Article 1 - Object and formation of the contract

The General Conditions of Purchase described hereafter detail the rights and obligations of ACTED Company (the Buyer) and the Seller within the framework of the performance of all the Orders placed by the Buyer.

A positive response to a Buyer's invitation to tender by the Seller or the acceptance of a Buyer's Order by the Seller shall constitute acceptance of these General Conditions of Purchase, supplemented by the Special Conditions of Purchase and/or the Purchase Order.

The General Conditions are the only contractual conditions applicable to purchases made by ACTED, the Seller waiving its own General Conditions of Sale.

Article 2 - Order

The Order shall be deemed accepted by the Seller when the Seller sends an acknowledgement of receipt of the Order to the Buyer. Any modification, even minor, of the Order must be subject to the prior agreement of the Purchaser by writing and an amendment to the Order.

Article 3 - Prices

The price agreed between the Parties on the day the Order is placed, and appearing in the Special Conditions and/or the Purchase Order, is firm and non-revisable, exclusive of taxes, in Euros, if not specified in the Purchase Order, global and fixed.

Article 4 - Delivery and reception

Delivery shall be made within the time limits, on the date and at the place indicated in the Special Conditions and/or the Purchase Order.

The deadlines, date and place of delivery are an essential part of the Order. They can only be changed with the Buyer's prior consent by writing.

The Buyer is only required to check the appearance and number of the parcels. The Buyer may send, by [communication format] to the carrier within three (3) working days, the reservations provided for in Article L.133-3 of the French Commercial Code.

The Buyer may refuse the receipt of defective products and request the return to the Seller so that these products may be replaced or, where applicable, reimbursed.

Article 5 - Warranties

The Seller undertakes to take the utmost care in the execution of the Order.

The Seller warrantee the Order, as from the effective delivery, against any lack of conformity with respect to the Purchase Order, and/or the contractual documents, and the trade rules. The Seller remains liable for all defects, including all faults, whether apparent or hidden.

The Contractor shall refrain from any form of abuse or child labour, from supporting or financing any act of terrorism, any form of money laundering, any form of fraud and corruption and any conflict of interest.

The Contractor acknowledges that it is aware of these values and commitments (as detailed here <u>https://www.acted.org/en/about-us/values-and-policies/code-of-conduct-and-policies/</u>) and undertakes to respect them, which constitute an essential condition of the Contract.

The Contractor is informed of the existence of the Transparency mechanism (<u>transparency@acted.org</u>) and acknowledges its duty to use it whenever there is a suspicion of behaviour contrary to the ethical values of ACTED.

Article 6 - Transfer of ownership and risks

The transfer of ownership shall occur in favor of the Buyer by the mere fact of the Seller acceptance of the Order. Any retention of title clause of the Seller shall not be invoked or enforceable against the Buyer, unless the Buyer has expressly accepted it in writing. The risks associated with the products are retained by the Seller until actual product delivery.

Article 7 - Invoicing and payment

Each invoice shall be issued by the Seller at the earliest on the day of the product delivery and shall be drawn up in accordance with the regulations into force on the issue date and the contractual documents.

Unless otherwise agreed between the Parties, and subject to the legal provisions, the invoice payment term is ninety (90) days end of month upon the invoices issue date.

Article 8 - Termination of the contract

The contract is concluded for the duration specified in the Particular Conditions and/or in the Purchase Order. Any extension or renewal of the contract must be subject to the signature of an amendment and/or a new Purchase Order.

In the event that the Buyer discovers any fault in the Seller's performance of the Order, the contract shall be considered null and void and the Buyer shall not be liable for any additional payment for the part of the Order which, if any, has not yet been performed. Neither Party shall be held liable for losses, costs, delays, and inability to perform the contract in case of force majeure. If force majeure period exceeds two (2) months, the Buyer reserves the right to terminate the contract without incurring penalties. **Article 9 - Liability and insurance**

The Seller shall be liable to the Buyer, without restriction or reservation, for the perfect execution of the obligations incumbent upon it by virtue of its contractual commitments with the Buyer, and for all the consequences that may result therefrom under the conditions of ordinary law. The Seller undertakes to compensate any damage caused to the Buyer or beneficiaries.

Any clause limiting the Seller's liability contained in the Seller's General Conditions of Sale or in any other similar document commonly used by the Seller shall be deemed unwritten for the performance of the Seller's contractual obligations with the Buyer. The Buyer's possible assistance during the Order execution shall in no way relieve the Seller of its liability.

The Seller holds insurance policies with notoriously solvent companies covering its operating and professional civil liability, guaranteeing it for a sufficient amount against the pecuniary consequences of the civil liability it may incur in case of personal injury, intangible, material and immaterial damage, whether consequential or not, caused to the buyer or to third parties, as a result of its products.

In addition, the Seller hold insurance policies covering its after delivery civil liability. The Seller shall provide the Buyer with the corresponding insurance certificate by the delivery date at the latest.



The fact of having the aforementioned insurance policies does not release the buyer from his liability, in particular with regard to damage not covered by the said policies or damage in excess of the sums guaranteed by the corresponding insurance policies]. Article 10 - Quality and compliance with the law

The Seller is responsible for the delivered product and provided services quality, which comply with the European and national regulations in force, particularly with regard to health, safety and the environment. The Seller declares to be in full compliance with the applicable social and fiscal legislation and vouch for the good behavior of its staff.

The Seller undertakes to set up a system for checking the conformity of the products with the General Conditions, Special Conditions, technical documents, standards and specifications of which the Seller is aware prior to the execution of the Order. The Seller undertakes to inform the Buyer of any products and services lack of conformity with the said documents and to compensate the Buyer for any harmful consequences resulting therefrom.

Article 11 - Jurisdiction and applicable law

This contract is governed by French law.

Any dispute relating to any of the contractual documents shall fall within the jurisdiction of the competent courts of Paris or of a mediator designated by the parties with a view to an amicable settlement.

IN WITNESS WHEREOF, the parties hereto, acting through their duly authorized representatives, have signed this Contract as of the date indicated below.

(company's legal representative or any other authorized person)

(position in the company)

As:

Duly authorized to signed on behalf of the Contractor:

Signature :



-BIDDER'S QUESTIONNAIRE ACTED [oPt] إستبانة معلومات

Date: 20/12/2020

Tender N°: T/HIP2021/EmergencyMaterials/RAM/20 -12-2020/001

PART I: INFORMATION	
A. Company Details and General Inform	nation
Name of Company	Trading As
Address	
(headquarters)	Telephone
Zip Code	
(headquarters)	Fax
City (headquarters)	E-mail address 1
PO Box	E-mail address 2
Country	
(headquarters)	Website address
Descrit Queen and a	Subsidiaries/
Parent Company or	Associates/ Overseas
name of owner	Representative
Sales Person's	Sales Person's
Name	Position
Sales Person's	Sales Persons' E-mail
phone	
Governance of the company: Chairmar	n, Vice-Chairman, Treasurer or Secretary of the Board of Directors or Board of
Trustees	
Name (as in	Date of birth
passport or other	(mm/dd/yyyy)
government-issued	
photo ID)	
Government-issued	Type of ID
photo Identification	
Document (ID)	
number	
ID country of	Rank or title in
issuance	organization
Other names used	Gender (e.g. male,
(nicknames or	female)
pseudonyms not	
listed as	
"Name")	



Current employer		Occupation	
and job title:		Cooupution	
Address of		Citizenship(s)	
residence			
Province/Region		E-mail address	
Is the individual a		Professional Licenses	
U.S. citizen or legal		- State Issued	
permanent	□Yes □No	Certifications	
resident?		Certifications	
	I ompany: CEO, Executive Director	 : Doputy Director Preside	unt or Vice President
Name (as in		Date of birth	
passport or other		(mm/dd/yyyy)	
government-issued		(11111/00/уууу)	
•			
photo ID) Government-issued		type of ID	
photo Identification			
Document (ID)			
number		Dank an title in	
ID country of		Rank or title in	
issuance		organization	
Other names used		Gender (e.g. male,	
(nicknames or		female)	
pseudonyms not			
listed as			
"Name")			
Current employer		Occupation	
and job title:			
Address of		Citizenship(s)	
residence			
Province/Region		E-mail addresses	
Is the individual a		Professional Licenses	
U.S. citizen or legal	□Yes □No	 State Issued 	
permanent		Certifications	
resident?			
Management of the co	ompany: Chief Finance Officer or		
Name (as in		Date of birth	
passport or other		(mm/dd/yyyy)	
government-issued			
photo ID)			
Government-issued		type of ID	
photo Identification			
Document (ID)			
number			



ID country of Rank or title in	
issuance organization	
Other names used Gender (e.g. male,	
(nicknames or female)	
pseudonyms not	
listed as	
"Name")	
Current employer Occupation	
and job title:	
Address of Citizenship(s)	
residence	
Province/Region E-mail addresses	
Is the individual a Professional Licenses	
U.S. citizen or legal	
permanent Certifications	
resident?	
Company's staff & insurance	
No. Full Time Employee average work wage per	
Employees: hour:	
% of Men to Any employee(s) with relatives	No
Women: working with ACTED?	
No. of Children: What is the legal minimum wage paid?	No
In what capacity? Are paid vacations offered?	No
What are their	No
ages?	No
Name of insurance Staff covered by health insurance?	No
company:	INU
Description of the Company	
Type of Business Manufacturing Manufacturing	
(multiple choices Consulting Company Trader	
possible):	
Sector of Business	
(multiple choices	
possible):	
Year Established: Country of registration:	
Licence number: Valid until:	
□ English □ Arabic	
Working languages:	
□ Spanish □ Other, please specify :	



Techn	ical	□ English		□ Arabic		
docum	nents	□ French		□ Chinese		
availa	ble in:	□ Spanish		Other, please	e specify :	
B. Fina	ancial Informatio	on			-	
VAT N	lumber:			Tax Number:		
-				Bank Account		
Bank I	Name:			Number:		
Bank /	Address:			Account Name:		
Swift/F	BIC number:			Standard Payment		
Ownut				Terms:		
			he last 3 years?		□Yes	□No
		of the compa	ny's most recent	Annual or Audited Financial	□ Attache	he
Repor						
	al Value of Total	Sales for the				
Year:			Year:		Year:	
USD:			USD:		USD	
	al Value of Expo	rt Sales for th				1
Year:			Year:		Year:	
USD:	:		USD:		USD:	
	perience	······································			and the iteration of the states	A
Comp	any s recent bus			er International Aid Agencies		s Agencies:
#	Organisation	Contact	Phone/E- mail	Goods/Works/Services	Value (USD)	Destination
#				G0003/ W01K3/ SEI VICES	value (USD)	Destination
	Organisation	person				
1	Organisation	person				
1 2	organisation	person				
1 2 3						
1 2 3 4						
1 2 3 4 5						
1 2 3 4 5 What i	is your company					
1 2 3 4 5 What i area o	is your company f expertise?	's main		Postriated to (coosify log		
1 2 3 4 5 What i area o	is your company of expertise?	/'s main	□ National	□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine	is your company f expertise? is your company ess coverage are	/'s main /'s ea?		□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine To wh	is your company of expertise? is your company ess coverage are ich countries ha	/'s main /'s ea? s your		□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine To wh	is your company of expertise? is your company ess coverage are ich countries ha any exported an	/'s main /'s ea? s your d/or		□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine To wh compa manag	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in t	/'s main /'s ea? s your d/or		□ Restricted to (specify loc		
1 2 3 4 5 What is area of What is busine To wh compa manag	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in the countries ha	/'s main /'s ea? s your d/or he last 3		□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine To wh compa manag years?	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in the e any other info	/'s main /'s ea? s your d/or he last 3 rmation		□ Restricted to (specify loc		
1 2 3 4 5 What is area of What is busine To wh compa manag years? Provid that de	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in the enonstrates you	/'s main /'s main /'s ea? s your d/or he last 3 rmation ir		□ Restricted to (specify loc		
1 2 3 4 5 What is area of What is busine To wh compa years? Provid that de compa	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in the emonstrates you any's qualificatio	rmation I's and		□ Restricted to (specify loc		
1 2 3 4 5 What i area o What i busine To wh compa years? Provid that de compa experi	is your company of expertise? is your company ess coverage are ich countries ha any exported an ged projects in the enonstrates you	rmation rs and by and rmation rs and rs and rs and rs and rs and		□ Restricted to (specify loc		



Organisations of which your							
company is a member							
D. Technical Capability							
Type of Quality Assurance			□ Attached				
Certificate							
Type of							
Certification/Qualification			□ Attached				
Documents							
International							
Offices/Representation							
	re Goods and/or Services your company sells:						
1)	6) T						
2)	7)						
3)	8)						
4)	9)						
5)	10) company (trucks & heavy machines, heavy & valuab	la aquinmont	nromicos 9				
warehouses, production site		ie equipment,	premises a				
1)	,						
2)	6) 7)						
3)	•						
4)	9)	8)					
5)	10)						
E. Miscellaneous	,						
Does your company have ar	n Environmental Policy? (Yes/No)	□Yes □]No				
Does your company have an Ethical Trading Policy? (Yes/No) □Yes □No □Yes □Yes □No □Yes □Ye							
Does your company have an Anti-terrorist Policy? (Yes/No)							
Is your company compliant with the EU General Data Protection Regulation (or							
equivalent)? (Yes/No)							
If you answered yes to the above two questions, please attach copies of your policy:							
Has your company ever been bankrupt, or is in the process of being wound up, having its affairs administered by the courts, has entered into an arrangement with creditors, has							
suspended business activities, is the subject of proceedings concerning these matters, or is \Box Yes \Box No							
in any analogous situation arising from a similar procedure provided for in national law?							
If you answered							
yes, please provide							
details:							
Has your company ever bee	n convicted of an offence concerning its professional	conduct by					
a judgment which as force o	•	-	□Yes □No				
If you answered							
yes, please provide							
details:							



Has your company ever been guilty of grave professional misconduct proven by other means?					□No		
If you answered							
yes, please provide	l						
details:							
Has your company ev	er not fulfilled its c	obligations relati	ing to the payment of social security	1			
	ontributions or the payment of taxes in accordance with the law of the country in which it is						
	hose of France, or those of the country where the contract is to be \Box Yes \Box N						
performed?							
If you answered				1			
yes, please provide	l						
details:	l						
Has your company ev	er been the subje	ct of a judgeme	nt, which has the force of res judicata				
• • •	•		tion or any other illegal activity?	□Yes	□No		
If you answered				1			
yes, please provide	l						
details:	l						
Has your company ev	er been declared	to be in serious	breach of contract for failure to				
comply with its contract	ctual obligations, f	following anothe	er procurement procedure or grant	□Yes	□No		
award procedure finar	-	-					
If you answered		•		1			
yes, please provide							
details:							
Has your company ever been declared to be in serious breach of contract for failure to							
comply with its contractual obligations, following another procurement procedure or grant							
award procedure financed by a donor country?							
If you answered							
yes, please provide							
details:							
Has your company ever been in any dispute with any Government Agency, the United							
Nations, or International Aid Organisations (including ACTED)?				□Yes	□No		
If you answered							
yes, please provide	l						
details:	l						
Do you agree with							
terms of payment of			Do you accept visit of ACTED staff	□Yes	□No		
30 days?	□Yes □	No	& external auditors to your office?				
PART II: CERTIFICAT	ION						
I, the undersigned warrant that the information provided in this form is correct, and in the event of changes, details							
will be provided to ACTED as soon as possible in writing. I also understand that ACTED does not do business with							
companies, or any affiliates or subsidiaries, which engage in any practices that are in breach of ACTED's Child							
Protection, Sexual Exploitation and Abuse Protection, Conflict of Interest, Anti-fraud, Anti-terrorism Policy and Data							
Protection Policies (available on request).							



Name: Da	te:	
Title/Position Pla	ice:	
E-mail address (for Sig	nature:	
contact for		
verification		
purposes):		
	mpany	
	imp:	
verification		
purposes): Check list of supporting documents		For ACTED use only
	☐ Attached	
2) VAT registration/tax clearance certificate	□ Attached	
3) Company profile	□ Attached	
4) Proof of trading/dealership/agent	□ Attached	Checked
5) Evidence of similar contracts	□ Attached	Checked
6) References	□ Attached	Checked
7) Particulars of CEO and key personnel	□ Attached	Checked
8) Articles of Association & Certificate of incorporation	□ Attached	Checked
9) Financial statements (latest)	□ Attached	Checked
10) Other (specify):	□ Attached	Checked
Name		الإسم

Position:	الوصف الوظيفي
Signature & Stamp:	التوقيع والختم
Date:	التاريخ



- BIDDER'S ETHICAL DECLARATION الإلتزام الأخلاقي

Date: 20/12/2020

Tender N°: T/HIP2021/EmergencyMaterials/RAM/20 -12-2020/001

اسم المورد Tenderer's name: _____

_____Tenderer's address: _____عنوان المورد

الرجاء قراءة الفقرات التالية جيدا والتوقيع على الإلتزام بها :CODE OF CONDUCT

1. Labour Standards

The labour standards in this code are based on the conventions of the International Labour Organisation (ILO).

• Employment is freely chosen

There is no forced, bonded or involuntary prison labour. Workers are not required to lodge `deposits' or their identity papers with the employer and are free to leave their employer after reasonable notice.

• Freedom of association and the right to collective bargaining are respected

Workers, without distinction, have the right to join or form trade unions of their own choosing and to bargain collectively. The employer adopts an open attitude towards the legitimate activities of trade unions. Workers representatives are not discriminated against and have access to carry out their representative functions in the workplace. Where the right to freedom of association and collective bargaining is restricted under law, the employer facilitates, and does not hinder, the development of parallel means for independent and free association and bargaining.

• Working conditions are safe and hygienic

A safe and hygienic working environment shall be provided, bearing in mind the prevailing knowledge of the industry and of any specific hazards. Adequate steps shall be taken to prevent accidents and injury to health arising out of, associated with, or occurring in the course of work, by minimising, so far as is reasonably practicable, the causes of hazards inherent in the working environment. Workers shall receive regular and recorded health and safety training, and such training shall be repeated for new or reassigned workers. Access to clean toilet facilities and potable water and, if appropriate, sanitary facilities for food storage shall be provided. Accommodation, where provided, shall be clean, safe, and meet the basic needs of the workers. The company observing the standards shall assign responsibility for health and safety to a senior management representative.

• Child Labour shall not be used

There shall be no new recruitment of child labour. Companies shall develop or participate in and contribute to policies and programmes, which provide for the transition of any child found to be performing child labour to enable her/him to attend and remain in quality education until no longer a child. Children and young people under 18 years of age shall



not be employed at night or in hazardous conditions. These policies and procedures shall conform to the provisions of the relevant International Labour Organisation (ILO) standards.

• Living wages are paid

Wages and benefits paid for a standard working week meet, at a minimum, national legal standards or industry benchmarks. In any event wages should always be high enough to meet basic needs and to provide some discretionary income. All workers shall be provided with written and understandable information about their employment conditions in respect to wages before they enter employment, and about the particulars of their wages for the pay period concerned each time that they are paid. Deductions from wages as a disciplinary measure shall not be permitted nor shall any deductions from wages not provided for by national law be permitted without the express and informed permission of the worker concerned. All disciplinary measures should be recorded.

• Working hours are not excessive

Working hours comply with national laws and benchmark industry standards, whichever affords greater protection. In any event, workers shall not on a regular basis be required to work in excess of the local legal working hours. Overtime shall be voluntary, shall not exceed local legal limits, shall not be demanded on a regular basis and shall always be compensated at a premium rate.

• No discrimination is practised

There is no discrimination in hiring, compensation, access to training, promotion, termination or retirement based on race, caste, national origin, religion, age, disability, gender, marital status, sexual orientation, union membership or political affiliation.

• Regular employment is provided

To every extent possible work performed must be on the basis of a recognised employment relationship established through national law and practice. Obligations to employees under labour or social security laws and regulations arising from the regular employment relationship shall not be avoided through the use of labour-only contracting, subcontracting or home-working arrangements, or through apprenticeship schemes where there is no real intent to impart skills or provide regular employment, nor shall any such obligations be avoided through the excessive use of fixed-term contracts of employment.

• No harsh or inhumane treatment is allowed

Physical abuse or discipline, the threat of physical abuse, sexual or other harassment and verbal abuse or other forms of intimidation shall be prohibited.

B. Environmental Standards

Suppliers should as a minimum comply with all statutory and other legal requirements relating to the environmental impacts of their business. Detailed performance standards are a matter for suppliers, but should address at least the following:

• Waste Management



Waste is minimised and items recycled whenever this is practicable. Effective controls of waste in respect of ground, air, and water pollution are adopted. In the case of hazardous materials, emergency response plans are in place.

• Packaging and Paper

Undue and unnecessary use of materials is avoided, and recycled materials used whenever appropriate.

Conservation

Processes and activities are monitored and modified as necessary to ensure that conservation of scarce resources, including water, flora and fauna and productive land in certain situations.

• Energy Use

All production and delivery processes, including the use of heating, ventilation, lighting, IT systems and transportation, are based on the need to maximise efficient energy use and to minimise harmful emissions.

• Safety precautions for transport and cargo handling

All transport and cargo handling processes are based on the need to maximise safety precautions and to minimise poential enjuries to ACTED beneficiaries and staff as well as the suppliers's employees or those of its subcontractors.

C. Business Behaviour

The conduct of the supplier should not violate the basic rights of ACTED's beneficiaries.

The supplier should not be engaged

1. in the manufacture of arms

2. in the sale of arms to governments which systematically violate the human rights of their citizens; or where there is internal armed conflict or major tensions; or where the sale of arms may jeopardise regional peace and security.

D. ACTED procurement rules and regulations

Suppliers should comply with ACTED procurement rules and regulations outlines in ACTED Logistics Manual Version 1.3. or above. In particular, ACTED's procurement policy set out in Section 2.1 and 2.4. (contract awarding). By doing so, Suppliers acknowledge that they do not find themselves in any of the situations of exclusion as referred to under section 2.4.2.

Operating Principles

The implementation of the Code of Conduct will be a shared responsibility between ACTED and its suppliers, informed by a number of operating principles, which will be reviewed from time to time.

ACTED will:

1. Assign responsibility for ensuring compliance with the Code of Conduct to a senior manager.

2. Communicate its commitment to the Code of Conduct to employees, supporters and donors, as well as to all suppliers of goods and services.

3. Make appropriate human and financial resources available to meet its stated commitments, including training and guidelines for relevant personnel.



4. Provide guidance and reasonable non-financial support to suppliers who genuinely seek to promote and implement the Code standards in their own business and in the relevant supply chains, within available resources.

5. Adopt appropriate methods and systems for monitoring and verifying the achievement of the standards.

6. Seek to maximise the beneficial effect of the resources available, e.g. by collaborating with other NGOs, and by prioritising the most likely locations of non-compliance.

ACTED expects suppliers to:

1. Accept responsibility for labour and environmental conditions under which products are made and services provided. This includes all work contracted or sub-contracted and that conducted by home or other out-workers.

2. Assign responsibility for implementing the Code of Conduct to a senior manager.

3. Make a written Statement of Intent regarding the company's policy in relation to the Code of Conduct and how it will be implemented, and communicate this to staff and suppliers as well as to ACTED.

Both parties will

1. require the immediate cessation of serious breaches of the Code and, where these persist, terminate the business relationship.

2. Seek to ensure all employees are aware of their rights and involved in the decisions which affect them.

3. Avoid discriminating against enterprises in developing countries.

4. Recognise official regulation and inspection of workplace standards, and the interests of legitimate trades unions and other representative organisations.

5. seek arbitration in the case of unresolved disputes.

Qualifications To The Policy Statement

The humanitarian imperative is paramount. Where speed of deployment is essential in saving lives, ACTED will purchase necessary goods and services from the most appropriate available source.

ACTED can accept neither uncontrolled cost increases nor drops in quality. It accepts appropriate internal costs but will work with suppliers to achieve required ethical standards as far as possible at no increase in cost or decrease in quality.

I undersigned [], agree to adopt the above Code of Conduct and to commit to comply with the labour and environmental standards specified, both in my own company and those of my suppliers.

الإسم والوصف الوظيفي للمورد والممثل الرسمي للشركة Name & Position of Tenderer's authorized representative

التوقيع Authorized signature



BIDDER'S CHECK LIST ACTED [oPt] - Lot 1 قائمة المحتويات

Date: 20/12/2020

Tender N°: T/HIP2021/EmergencyMaterials/RAM/20 -12-2020/001

BEFORE SENDING YOUR BIDDING DOCUMENTS, PLEASE CHECK THAT EACH OF THE FOLLOWING ITEM IS COMPLETE STAMPED SIGNED AND RESPECTS THE FOLLOWING CRITERIA: الرجاء التأكد من أن كل الوثائق المطلوبة المدرجة في الجدول تم إرفاقها وتوقيعها وختمها

Description		To be filled in by Bidder			only (to be filled in e Committee)	
		Included		sent	Comments	
1. PART 2 (form PRO-06) –Offer Form & attachments is attached, filled, signed, and stamped by the supplier. (compulsory) عرض السعر معبأ ، موقع ،مختوم ، مغلق من قبل المورد	Yes	No	Yes	No		
2. The prices in the Offer Form are in USD (compulsory) عرض السعر مدرج بالدولار الأمريكي						
3. PART 3 (form PRO-06-01)- Bidders Questionnaire Form is attached, filled, signed and stamped by the supplier. إستبانة العطاء مرفقة معبأة موقعة ومختومة من قبل المورد اذا وجدت						
 4. PART 4 – (form PRO-06-02) – Bidder's Ethical Declaration is attached, filled, signed and stamped by the supplier. (compulsory) إعلان الإلتزام الأخلاقي معبأ موقع ومختوم من قبل المورد 5. The Bidding documents are filled in 						
English. عرض السعر معبأ باللغة الإنجليزية 6. ANNEXES – Proofs of past performances in a similar field of activity (e.g. past deliveries of similar items) are provided شهادة خبرة وحسن آداء مرفقة						
7. ANNEXES – A Copy of Company registration documents and license are included & A copy of the legal representative ID. شهادة تسجيل وترخيص الشركة سارية المفعول مرفقة (مسمود)						
(compulsory) 8. ACTED-BOQ-drawings is attached, filled, signed and stamped by the supplier (compulsory) جدول الكميات و الرسومات						



9 ACTED_GCC_ is attached, filled, signed and stamped by the supplier الشروط العامة (compulsory)			
10. ACTED –			
المواصفاتGeneral Specification			
العامة (compulsory) is attached, filled, signed and stamped by the supplier			
11. ACTED-Technical Specification is attached, filled, signed and stamped by the supplier (compulsory) المواصفات الخاصة الهندسية			
المرفقات (compulsory) 12. Annexes-ACTED (compulsory) والتفصيلات			
 13. Tender entry guarantee worth 5,000 US \$ as bank a guarantee valid for 90 days starting from the closing date of the tender or a certified check bank (compulsory) 			
كفالة دخول عطاء بقيمة •••• دولار بصورة كفالة بنكية او شيك بنكي حيث لا تقبل الشيكات الشخصية			

الوصف الوظيفي للمورد والممثل الرسمي للشركة Name & Position of Bidder's authorized representative

التوقيع Authorized signature



Bidding Document for Emergency Project

2020-2021



Section I. General Conditions of Contract

These General Conditions of Contract, read in conjunction with the Particular Conditions of Contract and other documents listed therein, should be a complete document expressing fairly the rights and obligations of both parties.



Table of Clauses

11.	General			
1.	Definitions			
2.	Interpretation			
3.	Language and Law			
4.	Delegation			
B.	Works Control			
5.	Materials Supply, delivery and Installation			
6.	Subcontracting			
7.	Stockpiling and buffer Stock			
8.	Not-contracted Materials or Works			
9.	Access to the Site			
10.	Raw Materials Origin/Alternatives			
C. Time Control				
11.	Works Time frame delays Ordered by the Project Supervisor			
12	Management Meetings			
13.	Early Warning			
D.	Quality Control			
	-			
14.				
14. 15.	Identifying Defects			
	Identifying Defects Tests			
15.	Identifying Defects Tests Correction of Defects			
15. 16. 17.	Identifying Defects Tests Correction of Defects			
15. 16. 17.	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control			
15. 16. 17. E.	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control			
15. 16. 17. E. 18.	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control BOQs Price Variations			
15. 16. 17. E. 18. 19	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control BOQs Price Variations			
 15. 16. 17. E. 18. 19 20. 	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control BOQs Price Variations Payment Tax			
 15. 16. 17. E. 18. 19 20. 21 	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control BOQs Price Variations Payment Tax Currencies			
 15. 16. 17. E. 18. 19 20. 21 22. 23. 	Identifying Defects Tests Correction of Defects Uncorrected Defects Cost Control BOQs Price Variations Payment Tax Currencies			
 15. 16. 17. E. 18. 19 20. 21 22. 23. 	Identifying Defects			



26.	. Payment upon Termination	
G.	Safety Control	
28.	. Contractor's Risks	
29.	. Insurance	Error! Bookmark not defined.
30.	. Discoveries	



General Conditions of Contract

A. General

1. Definitions (a) The Works means the execution and completion of the supply, delivery, installation of the emergency response supplies and the remedying of any defects. Works are what the Contracting authority requires the Contractor to construct, install, and hand over to ACTED.

- (b) **The Bill of Quantities** means the priced and completed Bill of Quantities forming the Bid.
- (c) **The Completion Date** is the date of completion of the works as certified by the Project Technical Officer.
- (d) **The Contractor** is the party whose bid selected to carry out the works has been accepted by the contracting authority (ACTED).
- (e) **The Contract** is the contract between the contracting authority (ACTED) and the contractor to execute, complete, and maintain the works.
- (f) **The Contractor's Bid** is the completed bidding document submitted by the contractor to the contracting authority (ACTED).
- (g) **Days** are calendar days; **Months** are calendar months
- (h) Drawings mean the drawings of the works, as included in the contract, and any additional and modified drawings issued by (or on behalf of) ACTED in accordance with the contract, include calculations and other information provided or approved by the project manager/technical Officer
- (i) **A Defect** is any part of the Works not completed in accordance with the contract or not matching the technical specification, drawings and technical officer's instructions.
- (j) **Equipment** is the contractor's machinery, consumables and vehicles brought temporarily to the site to construct the works



- (k) **Materials** are all supplies including the 2 tender batches, , used by the contractor for incorporation in the works.
- (1) **The Project Manager** is the person named in the contract (or any other competent person appointed by ACTED and notified to the contractor) who is responsible for payments, project progress and administering the contract.
- (m) The Project Technical Officer is the person named in the contract (or any other competent person appointed by ACTED and notified to the contractor) who is responsible for supervising technically the execution of the Works and inspecting the implementation of the work to make sure it is completed in accordance with the technical requirements.
 - (n) **Specification** means the specifications of the works included in the contract and any modification or addition made or approved by the project manager & technical officer.
- (o) **A Subcontractor** is a person or corporate body who has a contract with the contractor to carry out fully/a part of the works in the contract, which could include materials manufacturing, transporting, delivery and installation or any needed works on the site.
- (p) **A Variation** is an instruction given by the Project Manager/Technical Officer which varies the Works.
- 2. Interpretation 2.1 In interpreting these general conditions of contract, words indicating one gender include all genders. Words indicating the singular also include the plural and words indicating the plural also include the singular. Headings have no significance. Words have their normal meaning under the language of the Contract unless specifically defined.
 - 2.2 The documents forming the Contract shall be interpreted in the following order of priority:
 - (a) Framework Agreement
 - (b) Awarding Letter
 - (c) Contractor's Bid
 - (d) Particular Conditions of Contract
 - (e) General Conditions of Contract
 - (f) Specifications



- (g) Drawings
- (h) Bill of Quantities
- (i) Others if needed.
- 3. Language and Law
 3.1 The language of the contract is English .The law that applies to the Contract is the law(s) in effect in parts of the West Bank and Gaza under the jurisdiction of the Palestinian Authority
- **4. Delegation** 4.1 The Project Manager/Technical Officer may delegate any of their duties and responsibilities to other partner (ACF, GVC, PUI), after notifying the contractor, and may revoke any delegation after notifying the contractor.

B. Works Control

- 5. Materials Supply, delivery and Installation
 5.1 The Contractor shall supply and install the supplies in accordance with the technical specifications and drawings respecting very strictly field delivery / installation guidelines and instructions. The contractor commits to supply, deliver and install the ordered material based on the drawings and specification included in the BOQs completely to the assigned sites.
 - 5.2 The contractor commits to follow strictly the instructions of contracting authority in case of security/legal concerns related to the delivery and installation of some orders. If needed the contractor commits to deliver the order materials outside the assigned site and send workers paid by him inside the site in order to help with installation. In addition the contractor commits to reimburse another party that ACTED assign to transport/Install the order supplies if needed
- 6. Subcontracting 6.1 The Contractor commits to subcontract person/corporate to carry out fully/a part of the works in the contract, which could include materials manufacturing, transporting, delivery and installation or any needed works on the site. This subcontracting body is supposed to be located in the opposite area of the contractor's manufacturing location. For example, if the contractor manufacturing spot is located in the north of West Bank, the contractor should be subcontracting another manufacturing company in the south of West Bank, and vice versa. The subcontracting agreement between the contractor and the subcontractor should be covering the same agreement period between ACTED and the contractor. Subcontracting agreement would be subject to the contracting authority technical inspection to check the subcontractor full ability of executing the works as needed. The cases were the contractor is allowed



to delegate part/the full works to the subcontractor would be defined and validated by the project manager.

7. Stockpiling and buffer Stock
The contractor is requested to constantly have buffer stocks, ready to be delivered and installed on demand. When an emergency phase is triggered by ACTED, ACTED will notify the contractor of the new buffer stock levels to have within a given period of time for a selection of items. Emergency phases can be triggered by ACTED at any time. When an emergency phase is triggered, it is expected that the contractor will be able to produce the following quantity of items per day:

• Emergency phase 1: 5 units of each size of residential and livelihood tents, 4 units of latrines, 50 water tanks, 10 units of each of the following livelihood equipment items: barriers, drinkers and troughs.

• Emergency phase 2: 10 units of each size of residential and livelihood tents, 10 units of latrines. The emergency phase 2 involves a 20% cost increase for the 6th to 10th identical tent items produced per day, and a 10% cost increase for the 6th to 10th latrines produced per day.

The agreed buffer stock levels will be formalized at the contracting stage , the contractor commits to keep the needed quantities matching the phase activated by the contracting authority

8. Not-contracted Materials or Works
 1.1 The Contracting authority may seek a quotation from the contractor's side in case of proposed Not-contracted Materials or works which are not included in the BOQs.

1.2 The Contractor shall be responsible for respecting the specifications, drawings of the Not-contracted Materials or Works and guidelines of the contracting authority.

1.3 Contractor offer for the execution of the Not-contracted materials or works, are subject to prior approval of the Project Manager/Technical Officer. The Contracting authority may assign the works execution to other party if needed.

9. Access to the Site The Contractor shall allow the Project Manager and Technical Officer and any person authorized by the contracting authority access to the site and to any place where work in connection with the Contract is being carried out or is intended to be carried out.





10. Raw Materials Origin/Alterna tives The Contractor should declare in the bidding docs the manufacturing raw materials origin and the alternative course in case of contractor's inability to obtain the raw materials from the original source.

C. Time Control

- 11.1 The contractor commits to complete the works by the Intended 11. Works completion date: The contractor may commence execution of the works on the Start date and shall carry out the Works in **Timeframe & Delays** accordance with the schedule defined by the Contractor, as Ordered by the updated with the approval of the Project Manager, and complete them by the Intended completion date. Any delay in executing the Project **Supervisor** works is subject to penalties. The Project Manager/Technical Officer may instruct the contractor to delay the start or progress of any activity within the works. Unless exceptional circumstances (risky area, difficult topography, communication difficulties with beneficiaries, etc.), the Intended completion date should be set no later than 7 calendar days after the purchase order has been made.
- 12. Management Meetings
 12.1 Either the Project Manager/Technical Officer or the Contractor may require the other to attend a management meeting. The business of a management meeting shall be to review the plans for remaining work and to deal with matters raised in accordance with the early warning procedure.
 - 12.2 The Project Manager/Technical Officer shall record the business of management meetings and provide copies of the record to those attending the meeting. The responsibility of the parties for actions to be taken shall be decided by the Project Manager either at the management meeting or after the management meeting and stated in writing to all who attended the meeting.
- **13. Early Warning** 13.1 The Contractor shall warn the contracting authority at the earliest opportunity of specific likely future events or circumstances that may adversely affect the quality of the work, increase the materials price, or delay the execution of the works. The Project Manager/Technical Officer may require the Contractor to provide an estimate of the expected effect of the future event or circumstance on the Contract Price and Completion Date. The estimate shall be provided by the Contractor as soon as reasonably possible.
 - 13.2 The Contractor shall cooperate with the Project Manager/Technical Officer in making and considering proposals



for how the effect of such an event or circumstance can be avoided.

D. Quality Control

- 14. Identifying Defects
 14.1 The Project Manager/Technical Officer shall check the Contractor's work and notify the contractor of any Defects that are found. Such checking shall not affect the Contractor's responsibilities. The Project Manager/Technical Officer may instruct the contractor to search for a defect and to uncover and test any work that the Project Manager/Technical Officer considers may have a defect.
- 15. Tests15.1 If the Project Manager/Technical Officer instructs the Contractor to carry out a test not specified in the specification to check whether any work has a Defect and the test shows that it does, the contractor shall pay for the test and any samples.
- 16. Correction of Defects16.1 The Project Manager/Technical Officer shall give notice to the contractor of any defects, and the Contractor should repair and fix it even after installation.
 - 16.2 Every time notice of a defect is given, the Contractor shall correct the notified Defect within the length of time specified by the Project manager's notice. Unless exceptional circumstances, the Defect should be fixed within 15 calendar days of the notification.
- 17. Uncorrected Defects17.1 If the Contractor has not corrected the defect within the time specified in the Project Supervisor's notice, the Project Manager shall assess the cost of having the defect corrected, and the contractor shall pay this amount, if not it would be deducted from his payment balance.

E. Cost Control

- 18. BOQs Price18.1 The Bill of Quantities shall contain priced items for the works to be performed by the Contractor. The Bill of Quantities is used to calculate the purchase order price. The Contractor will be paid for the quantity of the work accomplished at the rate in the Bill of Quantities for each item.
 - 18.2 Any delay in executing the works is subject to penalty charge equal 0.2% of the total amount of the Purchase Order per day but not exceeding 10% of its total amount.
- **19. Variations** 19.1 All Variations shall be included in updated agreement, and also in the activity schedule, produced by the Contractor.



	19.2	The Contractor shall provide the contracting authority with a quotation for carrying out the variation when requested to do so. The Project Manager/Technical Officer shall assess the quotation, which shall be given within seven (7) days of the request or within any longer period stated by the Project Manager/Technical Officer and before the variation is ordered.
]	19.3	If the Contractor's quotation is unreasonable, the contracting authority may order the Variation and make a change to the Contract Price, which shall be based on the Project Manager's own forecast of the effects of the Variation on the Contractor's costs.
1	19.4	If the Project Manager/Technical Officer decides that the urgency of varying the work would prevent a quotation being given and considered without delaying the work, no quotation shall be given and the variation shall be treated as a compensation Event.
1	19.5	The Contractor shall not be entitled to additional payment for costs that could have been avoided by giving early warning.
20. Payment	20.1	The Contractor shall submit to the contracting authority payment request along with delivery of the value of the works completed.
2	20.2	The contracting authority shall check the contractor's payment requests and certify the amount to be paid to the contractor, endorsed with the Project Manager.
2	20.3	The value of work executed shall be determined by the Project Manager.
2	20.4	The value of work executed shall comprise: the value of the quantities of work in the Bill of Quantities that have been completed
2	20.5	The value of work executed shall include the valuation of variations and compensation events.
2	20.6	ACTED will start processing the payment of an completed order after six months of supplies installation, and after the Project Manager/ Technical Officer endorsement.
21. Tax 2	21.1	The contractor should provide value added exempted payment requests to the contracting authority. Any unexampled payment request will not be considered. The contracting authority will not cover the cost of any taxes related to the supplies ordered.
22. Currencies	22.1	Payments are made in currencies of BOQ (USD\$)
23. Cost of Repairs	23.1	Loss or damage to the Works or Materials to be incorporated in the Works between the start date and the end of contract including



the Defects Correction periods shall be remedied by the Contractor at the Contractor's cost.

F. Finishing Works

- 24. Completion 24.1 The Contractor shall request the Project Manager/Technical Officer to issue a certificate of Completion/Reception voucher of the works endorsed, and the Project Manager/Technical Officer shall do so upon deciding that the whole of the Works is completed. The certificate of Completion/Reception voucher is only valid if the Project Manager has signed it, and the Contractor has signed and stamped it.
- **25. Termination** 25.1 ACTED may terminate the Contract if the other party causes a fundamental breach of the Contract.
 - 25.2 Fundamental breaches of Contract shall include, but shall not be limited to, the following:
 - (a) The Contractor stops work (stoppage has not been authorized by the Project Manager).
 - (b) The Project Manager/Technical Officer instructs the contractor to delay the progress of the works.
 - (c) the Project Manager/Technical Officer gives notice that failure to correct a particular defect is a fundamental breach of Contract and the Contractor fails to correct it within a specific period of time determined by the Project Manager
 - 25.3 If the Contract is terminated, the Contractor shall stop work immediately, make the Site safe and secure, and leave the Site as soon as reasonably possible.
- 26. Payment upon Termination If the Contract is terminated because of a fundamental breach of Contract by the Contractor, the Project Manager/Technical Officer shall issue a certificate for the value of the work done and Materials ordered less advance payments received up to the date of the issue of the certificate and less the percentage to apply to the value of the work not completed. All Materials on the Site, Temporary Works, and Works shall be deemed to be the property of the beneficiary if the Contract is terminated because of the Contractor's default.

G. Safety Control



27. Activities and Equipment Safety	The Contractor shall be responsible for the safety of all activities on the Site The contractor is responsible for the safety of his own equipment. The contracting Authority will not held responsible for any loss or damage of the contractors equipment
28. Contractor's Risks	From the Starting Date until the Defects Liability Certificate has been issued, the risks of personal injury, death, and loss of or damage to property (including, without limitation, the Works, Materials, and Equipment) are Contractor's responsibility
29. Discoveries	Anything of historical or other interest or of significant value unexpectedly discovered on the site shall be the defined and reported to the contracting authority. The contractor shall carry out the contracting authority's instructions for dealing with them.



Section II. Particular Conditions of Contract

The Agency is: **ACTED**

The Project Supervisor is Eng. Muhammad Abu-Rajab / ACTED

The Site is located at Area C – West Bank - Palestine

The Start Date shall be considered as per the date of the purchase order sent to the contractor

The language of the contract is **English**

The law that applies to the Contract is the law(s) in effect in parts of the

West Bank and Gaza under the jurisdiction of the Palestinian Authority

The Supervisor **may** delegate any of his duties and responsibilities.

The Contractor shall supply and install the required materials within **1-3 days** from the purchase order date.

The Contractor shall deliver the required response to the selected site and install it, under any conditions or circumstances (political, climate change .etc.)

The Defects Liability Period is: 365 days from the date of certificate of completion of the works

The currency of the Employer's country is: US Dollar

The Performance Security amount to be provided by the contractor is **10%** of total of the completed purchase orders in dollar

ACTED will start processing the payment of an implemented order (Supplied and installed) after three months from installation, and after the Project Supervisor

ACTED will not process any payment, if the contractor didn't deliver the required supplies to the selected area.

Delivering the supplies without installation is not allowed by the ACTED unless expectantly validated by project Supervisor

In such cases ACTED will deduct 25% from the supplies price, if the contractor delivers the required response without installation.

The Contractor shall submit a maintenance bank guarantee, which is **5** % of total contract price for **one year** after installation.

ACTED is not committed with the number of items in each BOQ.



General Specifications & Performance Requirements



SECTION ONE : GENERAL

1. Scope of work

These specifications cover the technical issues of the bid.

2. Drawings

2.1 Tender Drawings

The required number of contract Drawings are available at the date of Tender and are included in the list of Drawings attached to these Specifications. All work shall be performed in accordance with the Drawings Furnished together with the Contract Documents and any such additional drawings as may be issued by the Project Supervisor from time to time during the progress of the work or by the contractor as directed by the Engineer. Additional drawings which are required will be furnished to the Contractor in due time so as to enable him to perform the work shown thereon in its proper sequence and for any advance planning that may be necessary for the efficient performance of such work. The Project Supervisor will decide in such instance whether additional drawings are required for advance planning of the works and determine the time required for the same, and may request the Contractor to prepare such drawings.

2.2 Shop Drawings

If at any time before the commencement or during the progress of the work it appears to the Contractor that for the proper execution of a specific part of the Works, shop Drawings are necessary, these Drawings shall be prepared by the Contractor at his own expense and submitted to the Project Supervisor for approval. On the other hand, the Project Supervisor shall have authority to order at any time and the Contractor agrees to provide at his own expense any number of shop Drawings which, in the opinion of the Project Supervisor are necessary for the proper execution of a specified work. The Contractor shall not proceed with the above mentioned work unless these shop Drawings are approved by the Project Supervisor.

3. ABBREVIATIONS OF STANDARDS

The following abbreviations covering the Standards used for the works under the Contract shall have the significance set forth opposite each:



BS	British Standards Specifications
СР	Code of Practice
ASTM	American Society for Testing and Materials
ISO	International Standard Organization
LS	Local Standards

4. STANDARDS

The works have been designed to incorporate and utilize economically goods, materials and workmanship to various specifications which are detailed herein. Reference is commonly made to British Standards (BS) and British Standard codes of practice (CP) and local standards (LS) and to the American Society for Testing and Materials Standards (ASTM).

Different national or international standards (DIN or ISO etc.) that correspond to the specified Standard may be used provided that their requirements are not less stringent, and provided that the Contractor presents copies of such Standards translated into English. If any redesign of the works is necessitated by the adoption of such alternatives the costs incurred shall be borne by the Contractor. Those references shall in every case be deemed to include the latest edition or issue of such standards.

5. UNITS OF MEASUREMENTS AND ABBREVIATIONS

All units of weights and measurements shall be based on the Metric System of Weights and Measurements except standard products which may be expressed in nominal units of the Imperial System.

The metric terms and symbols occurring in the contract Documents are based on the "System International d'Unites" (SI System).

Description
Linear Meter
Square Meter
Cubic Meter
Kilogram
1000 Kilogram
Millimeter
Centimeter
Meter
Lump Sum

6. **DEFINITIONS**

Wherever the words defined in this section or pronouns used in their stead occur in the Contract Documents, they shall have the meanings herein given. As Directed, as Required, etc.



Wherever in the contract documents, or on the drawings, the words "as directed", as described "as ordered, "as requested," as required" "as permitted" or words of like import are used, it shall be understood that the direction description, order request requirements or permission of the Project Supervisor is intended. Similarly, the words approved, acceptable satisfactory and words of like import shall mean approved by acceptable to or satisfactory to the Project Supervisor.

Approved

This word when applied by the Project Supervisor to the Contractor's drawings or documents shall mean that the drawings or documents are satisfactory from the standpoint of interfacing with contractor's furnished components of the installations, and/or that the Project Supervisor have not observed any statement or feature that appears to deviate from the specification's requirements. Except for the interfacing with the contractor's furnished components, the contractor shall retain the entire responsibility for complete conformance with all of the Specification's requirements.

7 .INCONSISTENCY IN CONTRACT DOCUMENTS

The contractor shall execute the works according to the provisions of the contract documents. Any work indicated in one of the documents but omitted and/or not stated in one or more of the other documents shall be treated as though it were included in all of them.

If any two documents of the contract conflict as to the quantity of the work to be carried out, the discrepancy shall be brought to the notice of the Project Supervisor, who shall instruct the contractor which of the two conflicting documents to regard as correct.

If the contractor should discover that any work has been omitted and/or not indicated entirely or partially from all the documents, but that such work is essential to the safely or proper functioning of the works, he shall report the facts immediately to the Project Supervisor. If the work is something which in the opinion of the Project Supervisor could not have been foreseen by an experienced contractor, the Project Supervisor shall issue to the contractor a variation order stipulating the details of the work to be done.

Save as aforesaid in the above paragraph, no additional payment shall be made in respect of work carried out in connection with discrepancies between the various contract documents.

8. ERRORS IN COMPUTING CONTRACT DOCUMENTS

The contractor shall be responsible for any error which he makes in computing any quantities of material and labor required or costs involved or through any lack of knowledge of the site of misunderstanding of anything shown or implied on the drawings or in the specifications and/or the bills of quantities.

The contractor must refer any discrepancy in the drawings or the specifications to the Project Supervisor before proceeding in any of the works. The decision of the Project Supervisor as to the interpretation of the discrepancy will be final.

Any item or items of work not specifically shown on the drawings or referred to in the specifications but which would be necessary for the proper construction of the works in accordance with the best practice is implied and must be included for as incidental to the



contract price. Any item for which the contractor has not inserted a price in the Bills of quantities shall be deemed to be covered by other prices or rates therein.

9. TEMPORARY WORKS AND REINSTATEMENT

The contractor shall provide and maintain all temporary roads and tracks necessary for movement of plant and materials and clear same away at completion and make good all works damaged or disturbed.

The contractor shall submit drawings and full particulars of all temporary works to the Project Supervisor before commencing same. The Project Supervisor may require modifications to be made if he considers them to be insufficient and the contractor shall give effect to such modifications but shall not be relieved of his responsibilities for the sufficiency thereof.

The contractor shall provide and maintain weatherproof sheds for storage of materials pertinent to the works both for his own use and for the use of the employer and clear same away at the completion of the works.

The contractor shall divert as required, at his own cost and to the approval of the Project Supervisor, all public utilities encountered during the progress of the works, except those specially indicated on the drawings as being included in the contract.

Where diversions of services are not required in connection with the permanent works, the contractor shall uphold, maintain and keep the same in working order in existing locations.

The contractor shall make good, at his own expense, all damage to telephone, telegraph and electric cables or wires, sewers, water, or other sewers, except where the public Authority or private party owning or responsible for the same elects to make good the damage. The cost incurred in so doing shall be paid by the contractor to the public Authority or private party on demand.

All injury to the surface of the land, to the beds of water-courses, projecting banks, etc., where disturbed by the works (other than where specifically ordered by the Project Supervisor) shall be repaired by the contractor or the authorities concerned, at the contractor's expense. All such making good shall be to the approval of the Project Supervisor.

The requirements detailed above shall be provided and maintained at the expense of the contractor.

The employer shall not be liable for loss or injury to any temporary works.

10. EXISTING FACILITIES

The existing facilities services must be kept in continuous operation throughout the construction period. No interruption will be permitted which adversely affects the degree of service provided. Provided permission is obtained from employer and Project Supervisor in advance, portions of the existing facilities may be taken out of service for short periods corresponding with period of minimum service demands. Such permission will not relieve the contractor of any of his responsibilities under this contract.

11. LINES AND GRADES

The contractor shall keep the Project Supervisor informed, a reasonable time in advance, on the times and places at which he intends to do work, in order that lines and grades may be



established and necessary measurements for record and payment made with a minimum of inconvenience to the Project Supervisor or delay to the contractor. The contractor shall have no claim for damages or extension of time on account of delays in the giving of lines and grades, making record measurements or destruction of such marks and the consequent necessity for replacement.

The Project Supervisor will furnish the contractor with such basic lines and grades as he, the Project Supervisor, deems necessary, but this shall not be construed to mean all lines, grades, elevations and measurements. It shall be the contractor's responsibility before commencing any section of the work to establish and locate the permanent bench marks to be used through proper survey procedures. The contractor shall refer all temporary bench marks thereto.

The contractor shall be responsible for the stake-out survey for construction purposes and the replacement of monuments and property markers disturbed by the work. The survey shall proceed in advance of the construction at a rate satisfactory to the Project Supervisor. The contractor shall keep the Project Supervisor fully informed as to the progress of the stake-out survey.

The exact position of all work shall be established from control points which are established by the contractor and approved by the Project Supervisor if necessary the Project Supervisor may modify such points. Any error, apparent discrepancy or omission in the data shown or required for accurately accomplishing the stake-out survey shall be referred to the Project Supervisor who shall take whatever corrective measures he deems necessary.

The contractor shall be responsible for the accuracy of his work and shall maintain all reference points, stakes, etc., throughout the life of the contract. Damaged, destroyed or inaccessible reference points, bench marks or stakes shall be replaced by the contractor. Existing or new control points that will be or are destroyed during construction shall be re-established and all reference ties recorded therefore shall be furnished to the Project Supervisor. All stake-out survey work shall be referenced to the bench mark and manhole centers given by the Project Supervisor.

All computations necessary to establish the exact position of the work from control points shall be made and preserved by the contractor. All computations, survey notes and other records necessary to accomplish the work shall be neatly prepared and made available to the Project Supervisor upon request or furnished upon contract completion.

All instruments, equipment stakes and other material necessary to perform the work shall be provided by the contractor.

All stakes used shall be of a type acceptable to the Project Supervisor, clearly and permanently marked so as to be legible at all times. It shall be the contractor's responsibility to maintain these stakes in their proper position and location at all times. Any existing stakes or markers defining property lines and survey monuments which may be disturbed during construction shall be properly tied in to fixed reference points before being disturbed and accurately reset in their proper position upon completion of the work.

The Project Supervisor may check all or any portion of the stake-out survey work or notes made by the contractor and any necessary correction to the work shall be immediately made. Such checking by the Project Supervisor shall not relieve the contractor of any responsibilities for the accuracy or completeness of his work.



12. WATER FOR THE WORKS

The contractor shall provide all necessary water for the works and tests, with all temporary plumbing and storage, pay all charges, and alter, adapt and maintain temporary work as necessary and remove and make good at completion.

13. ELECTRICAL POWER AND LIGHTING FOR THE WORKS

The contractor shall provide all necessary artificial lighting and power for the execution and security of the works and for protection, with all meters, temporary wiring and fittings, etc., pay all charges, and alter, adapt and maintain the temporary work as necessary and remove and make good at completion.

14. MEDICAL FACILITIES

The contractor shall arrange for medical attention to be available when necessary and shall provide dressing stations complete with all adequate first aid equipment within easy access of each works area on the site. The contractor shall display in suitable places the names of his employees who are available from time to time to render first aid. The contractor shall provide for the transport of serious cases to the nearest hospital.

15. CUSTOMS AND LOCAL DUES

All state dues, tolls rates, duties, fees and charges in connection with the works shall be deemed to be included by the contractor in his contract unit Rates.

16. MATERIALS, GOODS AND WORKMANSHIP

Materials, goods and workmanship shall be of the best quality of their respective kind. The contractor shall carry out everything necessary for the proper execution of the works, whether or not shown on the Drawings or described in the specifications.

17. SPECIFIED MANUFACTURER'S PRODUCTS

Manufacturer's name or catalogue number, if shown in the specification or indicated on the Drawings, are given only for indicative purpose and for general reference only. It shall be understood that the actual material supplied shall meet the requirements of the specifications, and if necessary, the material specified under such manufacturer's name or catalogue indicated for reference, shall be modified under the direction of the Project Supervisor.

Provided always that such modified material shall meet the requirements of the specified material together with the requirements of other materials specified for other trades in these specifications under the direction of the Project Supervisor.

Any modification under such conditions shall not give the right to the contractor to claim against any loss or extra cost incurred.



18. ALTERNATIVE MATERIALS

Should the contractor wish to offer alternative items or materials to those specified he shall supply details of such alternatives together with details of any reduction in the contract price should the alternative be allowed to be substitute for the specified items or materials. All offered alternatives shall comply fully in all respects with the specifications of the particular items or materials. Acceptance or refusal of such alternatives will be entirely at the discretion of the Project Supervisor.

If during the course of the contract certain materials or items required for use in the works should be unobtainable, despite the best effort of the contractor, the contractor may offer for the approval of the Project Supervisor alternative materials or items, provided that they possess the minimum requirements of the originally specified material.

In the event of acceptance of any alternative materials or items a suitable price reduction shall be made in respect of any decrease in value but no price addition shall be made in respect of increase in value.

In the event of refusal of any alternative materials or items the contractor shall not be relieved of any of his obligations under the contract and shall be solely liable for any delay or loss occasioned by his failure to provide the material or items as specified.

19. PERIODIC REPORTS

The contractor must present to the Project Supervisor's representative detailed reports and schedules as stipulated in the conditions of contract.

The contractor shall prove to the Project Supervisor's representative upon his request the correctness of the above mentioned reports without having the right to use such documents to support a claim for any extra payment or compensation whatsoever in regard or in relation to such reports.

20. SITE PROGRESS MEETINGS

During the course of the work, site progress meetings shall be held at regular intervals at least once every week in the presence of the Project Supervisor for the purpose of coordinating the contractor's works and to insure that full compliance with the various sequences of the contract are maintained. Minutes of such site meetings will be recorded, copies will be distributed to all persons concerned and full effect shall be given to all instructions contained herein.

Prior to such meetings the contractor shall give to the Project Supervisor's representative details in writing of that portion of the works he proposes to construct during the coming two weeks with details of the plant and methods he proposes to employ. These proposals shall be discussed at the meeting and no work based on such proposal shall proceed without the approval of the Project Supervisor's representative.

The contractor shall have no claim against the employer for costs incurred by him in changing the method of working or in the provision and use of other additional plant.



21. CANCELLATION DUE TO SLOW PROGRESS

If the Project Supervisor shall be of the opinion that having regard to the state of the works at any time, the contractor will be unable to complete any section of the works by the time specified or by such extension thereof as he may be entitled to under the contract and the contractor has failed to carry out steps and to expedite the work in accordance with the conditions of contract or, if the Project Supervisor is of the opinion that such steps are inadequate, the Project Supervisor may by written order omit the whole or any part of the uncompleted work included in that section and the employer shall be at liberty to execute such omitted work by his own workmen or by other contractors. If the cost of such omitted or uncompleted work shall exceed the sum which would have been payable to the contractor on due completion of the said work, then the contractor shall, upon demand, pay to the employer the amount of such excess and it shall be deemed a debt due by the contractor to the employer and shall be recoverable accordingly.

22.PROTECTION FROM WEATHER AND FLOODS

The contractor shall keep the works well drained until the Project Supervisor certifies that the whole of the works is substantially complete and shall ensure that so far as is practicable all work is carried out in the dry. Excavated areas shall be kept well drained and free from standing water.

The contractor shall construct, operate and maintain all temporary dams, watercourses and other works of all kinds including pumping and well point dewatering plant that may be necessary to exclude water from the works while construction is in progress. Such temporary works and plant shall not be removed without the approval of the Project Supervisor's representative.

Notwithstanding any approval by the Project Supervisor of the contractor's arrangements for the exclusion of water, the contractor shall be responsible for the sufficiency thereof and for keeping the works safe at all times particularly during any floods and for making good at his own expense any damage to the works including any that may be attributable to flood. Any loss of production or additional costs of any kind that may result from floods shall be at the contractor's own risk.(Without any compensation)

23. CLEARING AWAY

The contractor shall take down and clear away all plan and temporary works, including sheds, mess rooms, sanitary conveniences, offices, latrines, sign-boards, and other temporary works, unless otherwise described, and make good.

The contractor shall remove all existing rubbish and debris and surplus materials from the site as they accumulate and at completion, and clean all surfaces, including those of the affected portions of the existing premises, internally and externally, remove stains and touch up paint work and polished work, and leave the works clean and to the satisfaction of the Project Supervisor at completion.



24. TESTS FOR WATERT LEAKAGE OF STRUCTURES

When ordered by the Project Supervisor the structures shall be tested with water by the contractor.

The structure when filled shall satisfy the test if at the end of one week no leakage is apparent.

25. TESTING ON COMPLETION

The Project Supervisor may before issuing the certificate of completion require any part of the works to be tested for conformity with the specification. Such tests shall be made at the contractor's expense.

26. INSPECTION

If work to be done away from the construction site is to be inspected on behalf of the employer during its fabrication, manufacture, or testing, or before shipment the contractor shall give notice to the Project Supervisor of the place and time where such fabrication, manufacture, testing, or shipping is to be done. Such notice shall be in writing and delivered to the Project Supervisor in ample time so that the necessary arrangements for the inspection can be made.

In respect of all items of equipment and materials to be imported for incorporation in the permanent works the contractor shall submit to the Project Supervisor's representative in the English language inspection and test reports issued in the country of origin and certified by an independent inspector or inspection firm of international repute approved in advance by the Project Supervisor. The reports shall certify that all such items are in full compliance with the contract requirements and specifications and shall be accompanied by full details of sampling, inspection and test results. Each such report shall be submitted prior to the shipment of the related items to the site.

No extension of time on account of delays due to inspection shall be granted as such time as is needed for inspection shall be considered to have been considered in the schedule of the works.

Material and equipment procured within the country for incorporation in the permanent works shall be inspected at the place of origin by competent and experienced specialized personnel appointed by the contractor and approved by the Project Supervisor. Inspection and test reports certifying that the related item is in full compliance with the contract requirements and specification shall be submitted prior to its incorporation in the works.

The certification herein prescribed shall be submitted whether or not the Project Supervisor or his representative has exercised the right to witness test or make inspections at the point or origin. The Project Supervisor shall be entitled to apply the conditions of contract in respect of items not so certified. Certification shall be furnished at the contractor's expense. It shall not relieve the contractor of the obligation to ensure that all material and workmanship



incorporated in the works shall be in full compliance with the contract requirements and specification at the time of final handing over of the completed works.

27. PROTECTION OF FINISHES

The contractor shall take every care to prevent damage to the works from whatever cause and shall ensure that adequate protection is given to all works from the activities of following trades and nominated subcontractors. Vulnerable parts of the work particularly liable to damage shall be protected as may be reasonably required by the Project Supervisor's representative.

28. PROTECTIVE EQUIPMENT AND CLOTHING

The contractor shall provide and maintain all necessary protective and safety equipment and clothing for the operative and site staff.

29. METHODS OF MEASUREMENT AND PAYMENT

29.1 Description

This section covers methods of measurement and payment for items of work under this contract.

The total tender price shall cover all work required by the contract documents. All costs in connection with the proper and successful completion of the work, including furnishing all materials, equipment supplies, and appurtenances; providing all construction plant, equipment, tools, testing ,and performing all necessary labor and supervision to fully complete the work, shall be included in the unit price and lump sum price bid. All work not specifically set forth as a pay item in the Bill of Quantities shall be included in subsidiary obligation of contractor and all costs in connection therewith shall be included in the prices bid.

29.2 Quantities

All estimated quantities stipulated in the tender form or other contract documents are approximate and are to be used only (a) as a basis for estimating the probable cost of the work and (b) for the purpose of comparing the bids submitted for the work. The actual amounts of work done under unit price items may differ from the estimated quantities. The basis of payment for work will be the actual work done and paid using the unit price rate (re-measured) .Contractor agrees that he will make no claim for damages, anticipated profits, or otherwise on account of any difference between the amounts of work actually performed and the estimated amounts.

30. DEMOLISHED MATERIAL:



The contractor shall at his expense progressively remove transport out of the site to approved dump site all surplus materials rubble and debris from the site.

31.QUALITY OF WORKS AND MATERIALS (SAMPLES)

The contractor shall submit samples of materials the contractor intends to use within the project, all such materials should be tested through a competent laboratory with a wide reputation to enable the supervisor to issue his approval in due time before incorporating these materials in the work. Should in the supervisor's opinion the samples so prepared by the contractor, not meet the requirements of the specifications, the contractor shall prepare a new sample until it is approved by the Project Supervisor, such approval will never relieve the contractor from any of his obligations. All costs in connection with preparing the said works samples under the provisions of this clause shall be at the contractor's expense.

32.TEST'S RESPONSIBILITY

The contractor shall be responsible for all the obligations in concern with tests required throughout the specifications and the supervisor's instructions, tests shall be made at the contractor's expense, obligations in concern of the tests needed for quality control arrangements, all the tests should be carried out by a competent laboratory having a very wide reputation and to be in previously approved by the supervisor. If the result of any of the tests required does not meet entirely or partially the technical specification, all the defected works should be removed and replaced making good and retested, the contractor shall bear the full responsibility of the entire obligations of the costs of removal, replacing, making good, test expenditures at the contractor's own expense.

33.SITE INVESTIGATION

The contractor shall be deemed to have visited the site of works and satisfied himself to the nature of the ground and made himself conversant with the local condition to be encountered during the execution of each contract, and his unit rates in the bill of quantities have included all the necessary cost to execute the works.



Technical Specifications

1. CONCRETE

1.1 General

Unless otherwise authorized by the Project Supervisor, concrete shall be machine mixed. The mixing of concrete or mortar shall not be permitted when the temperature is above 40 C or when the temperature is below 5 C.



1.2 Mixing on Site

- Concrete shall be thoroughly mixed in a batch mixer conforming to the requirements of B.S. 1305 Batch type concrete mixers which will ensure a uniform distribution of the materials throughout the mass.
- All concrete shall be mixed for a period of not less than 1 ½ minutes after all materials, including water, are in the mixer. During the period of the mixing the mixer shall operate at the speed for which it has been designed, but this speed shall be not less than 14 nor more than 20 revolutions per minute.
- The first batch of concrete material placed in the mixer shall contain sufficient excess of cement, sand and water to coat the inside of the drum without reducing the required mortar content of the mix. Upon the cessation of mixing for a considerable period, the mixer shall be thoroughly cleaned.

2. METAL WORKS

2.1 Scope

- These specifications cover ferrous and non-ferrous works intended to be used in the project; all in accordance with the Drawings and as directed by the Project Supervisor.
- The contractor shall ensure of all dimensions on the site and clear them in detailed shop drawings for approval by the Project Supervisor.
- The contractor should provide the Project Supervisor with detailed shopdrawings for aluminum works that will be installed, in addition to providing samples of profiles, method of statement, accessories and hardware in order to have a written approval prior to starting.

2.2 Materials

2.2.1 Steel

Steel plates, and structural steel shaped sections shall conform to the requirements of edition for structural sections.

2.2.2 Aluminum

The Aluminum used should be approved type by the Palestinian Standards Institute, as indicated in the specifications and Bill of Quantities.

2.2.3 Bolts, Nuts and Washers

- Bolts and nuts shall conform to the requirements of (British Standard)B.S. 4190: I.S.O. metric black hexagon bolts, screws and nuts.(PTA Brand)



- Plain washers shall be made of steel. Taper or other specially shaped washers shall be made of steel or malleable cast iron and shall conform to the requirements of B.S. 4320, metal washers for general Project Supervising purposes.

2.2.4 Galvanized Steel Pipes

Galvanized steel pipes shall conform to the requirements of B.S. 1287 - I.S.O. "Medium Series".

2.3 Description of Steel

- Steel to be used for all the works must be new and have never used before and must be free of rust and crusts. The steel bar, beam or plate should not be welded pieces but one unit.
- The steel profiles and tubes used should be sound and free of defects like buckling, bending, and cracking or other. The tolerances in sections of steel shall not more than 0.30 mm for thickness and 0.50 mm for other dimensions.

2.4 Description of Aluminum

- All of aluminum profiles should be according to the drawings and not be less than the following:

1. The thickness of aluminum profiles used for sliding doors and windows should not be less than $(2mm\pm0.1)$

2. The thickness of aluminum profiles used for hinged doors and windows should not less than 2 mm.

3. The thickness of powder coating at profile should not less than 60 micron at least.

2.5 Manufacturing and fixing of steel works:

2.5.1 General

- The Contractor shall be responsible for the correctness and accuracy of the dimensions of the finished items. He shall therefore carefully check the dimensions indicated on the Drawings, verify any change and ascertain the sizes on the site which will enable him to prepare final working drawings for fabrication and erection purpose.
- Such drawings shall be submitted to the Project Supervisor for his verification and approval.
- Fabrication orders can only take place after the contractor obtains, in writing, the approval of the Project Supervisor for the drawings.

2.5.2 Hollow Metal Door Frames

Hollow metal door's frames shall be made of the profiles and sizes shown on the drawings and obtained from an approved manufacturer. The door frames shall be with minimum 3.0 mm thick, twice laminated steel sections and be delivered to site complete with a factory applied anti-corrosive plastic coating., ties cast to backs of frames for building in and rubber silencers on the frame.

2.6 Workmanship2.6.1 Aluminum elements



- The glass used should be transparent glass with a thickness of 4 mm or if stated otherwise.
- The Aluminum used is coated with hot dipped polyester powder (paint thickness should not less than 60 microns).
- Aluminum should be colored type and color choice as instructed by supervisor Project Supervisor.
- Those screws should have enough size and length to fix the frames strongly as required and the approval of Project Supervisor.
- The hardware and accessories should be made of aluminum (Allen key corners, rails, locks, handles... etc.) of the same type of profiles required and shall be of solid hardware durable and shaped.
- The used wheel rollers should be spherical ball bearing.
- The locks should be secured and from approved type by the Project Supervisor.
- The closing kit and tapes used to prevent water and air leakage.
- The Project Supervisor approval should be obtained for the color and appearance of the coating surface of aluminum before industrialization and supplying materials.
- Gap spaces between aluminum and architectural openings for doors and windows should be packed with a silicon paste injected from both sides to ensure full closure. The color of silicon must be fit to the color of aluminum.
- The contractor is responsible for all works of aluminum during and after installation until handing over the project.
- Installation of glass must be using strip of rubber between aluminum and glass from inside and outside.

2.6.2 Steel elements

- All steel works should be done with professional manner and welding must be hidden, not appeared on the face and polished.
- All steel parts shall be accurately set out, cut, framed, assembled and executed using proper bolts or welding electrodes.
- All cut parts shall be sawn cut; no oxygen burning shall be permitted except for pipe supports.
- All welding shall be electrical welding, clean and of proper workmanship. All cut parts and welded sections shall be ground, even and filed smooth with rounded edges.
- No allowable showing any signs of knocks or any type of cavity in steel and should be all contact links arbitrator well without leaving any vacuum or clear signals welding redundant on the face
- Costs of making holes well done and recovered are responsible of contractor with his own costs.
- Making doors and windows accurately and proficiently duly taking into account that are made all welding by professionals and skilled labors with expertise in this area, and automatically clean all welded links and to get a smooth surface without protrusions Stored all produced parts prior to installation in a dry place and the process of being transfer without scratches.
- The contractor shall provide samples of any section for approval by Project Supervisor before Fix door's frames.



- All work shall be erected plumb and true to lines and rigidly secured to walls, floors or ceilings as shown on Drawings and to the satisfaction of the Project Supervisor.
- Welding work is along the flat welding (stitching along the line of welding)

2.6.3 Welding

- Welding surfaces shall be clean, free cobalt, rust and other materials that will have the opposite effect on the welding by skilled professionals with expertise in this area.
- Prohibits a welding operations in the up-normal weather conditions such rain, strong winds, or when temperatures fall to zero (0 °c), unless action was taken to ensure that the impact of these conditions on welding operations, and the approval of Project Supervisor.
- The intensity of electricity used in welding operations shall be located within the established range of welding rods, and then welding process is the movement of fluctuations consecutive start of the first welding and so close, and being removed from the slag welding operations abreast so that each layer of the welding layers completely clean before the following class action.
- Prohibits any subsequent operations for one welding process unless after the disclosure of welding by Project Supervisor and approval, and is not being disclosed mentioned before passing 72 hours after the end of operations.
- Must provide workers with masks, protective glasses and gloves, and necessary to safe them during welding operations.
- Welding work is along the flat welding (stitching along the line of welding).

2.7 Galvanized steel covers

- Galvanized steel covers shall be galvanized mild steel with raised threads of Durbar pattern or similar approved by the Project Supervisor.
- The covers shall support on galvanized mild steel frames. The frames shall have mitered and welded corners, with welded fishtail anchors at not greater than 1m centers, all galvanized after fabrications.

3. ROOFING, WATERPROOFING AND THERMAL INSULATION

3.1 Preparation

- All surfaces must be clean sound, and free from oil, grease and all loosely adherent materials.
- Wire brush, sand blast or grit blasting may be used to remove any surplus adhered to steel.
- The contractor must submit a request for all materials for Project Supervisor approval.

3.2 Materials

3.2.1 Rubber

The rubber water-stop shall be fabricated from a high-grade, tread-type compound. The basic polymer shall be natural rubber or a synthetic rubber.

3.3 Thermal Insulation



Criteria, design aspects, implementation methodology and relevant materials of the thermal insulation must be according to the Palestinian Code for Energy Efficient Building and using the supplementary Guidelines.

4. PLUMPING AND SANITARY INSTALLATIONS

4.1 Drainage and Waste Systems

- These systems shall be subject to a water test prior to being covered and also tested for water tightness after backfilling.
- On any section of the pipe under test the head of water applied shall not be less than 3.00 meters and not greater than 6.00 meters. Tests shall be maintained for 20 minutes, and any defects shall be rectified and the test reapplied to the complete satisfaction of the Project Supervisor.